

Code: NVR4416-16P-I

# NVR NVR4416-16P-I 16 CHANNELS +16-PORT SWITCH POE DAHUA

Net: 1 099.26 EUR Gross: 1 099.26 EUR



## SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 8.3 Mpx, 4K UHD - 3840 x 2160 px
Video outputs:	1 pcs HDMI 4K 1 pcs VGA
Audio support:	16 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Supported hard drives:	4 x 8 TB SATA III
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Center, IP Search, P2P, ONVIF
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function
Bitrate:	max. 200 Mbps
Network functions:	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
ONVIF:	2.4
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>  See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Default IP address:	192.168.1.108
Default admin user / password:	admin / -
Web browser access ports:	80, 37777

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

PC client access ports:	37777
Mobile client access ports:	37777
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Alarm inputs / outputs:	16 / 4
PTZ control:	✓
Motion Detection:	22 x 18 motion zones
USB:	1 pcs USB 2.0 1 pcs USB 3.0
Intelligent image analysis:	✓
Mouse support:	✓
IR remote controller in the set:	—
Main features:	<ul style="list-style-type: none"> <li>• Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians,</li> <li>• Support for devices with the ANPR vehicle identification functions and face recognition,</li> <li>• Identification of the type of the observed object (human, vehicle),</li> <li>• Face recognition and analysis in real time (up to 12 photos per second) : <ul style="list-style-type: none"> <li>- Comparison of faces with images from the database</li> <li>- Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask)</li> <li>- Real-time search of people on the basis of given side information in the range corresponding to features recognized by artificial intelligence of the device</li> <li>- Face bases can be used globally or locally for one video channel - depending on the need</li> <li>- In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number</li> </ul> </li> </ul>
Switch PoE:	<ul style="list-style-type: none"> <li>• 16-port PoE Switch built-in, 25.5 W / Channel - PoE (802.3af/at), max. 150 W (total)</li> <li>• ePoE - 800 m : 1 ... 8 ports</li> </ul>
Power supply:	230 V AC
Weight:	4.82 kg
Dimensions:	440 x 411 x 76 mm
Supported languages:	Polish, English
Country of origin:	China
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>

## PRESENTATION



Front panel:




Rear panel:



Example captures of device interface:



In the kit:



**OUR OPINIONS**



- Audio transmission via network.
- The NVR4416-16P-I is equipped with USB 3.0 port allowing to fast records backup.
- LAN Gigabit interface.

**PACKAGE**

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60