

Code: APTI-N2502-4KS3

NVR **APTI-N2502-4KS3** 25 CHANNELS

Net: **85.41 EUR** Gross: **85.41 EUR**

The APTI-N2502-4KS3 digital recorder is a professional device using in IP surveillance systems.

The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 8.8 Mpx - 4096 x 2160 px - Supports up to 12 cameras 5 Mpx - Supports up to 20 cameras 4 Mpx - Supports up to 25 cameras 3 Mpx - Supports up to 25 cameras 1080p - Supports up to 25 cameras 1.3 Mpx - Supports up to 25 cameras 720p - Supports up to 25 cameras
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	25 Channels - Audio from cameras
Audio inputs:	—
Audio outputs:	1 pcs Cinch socket
Image compression method:	H.265+ / H.265 / H.264+ / H.264
USB:	• 1 pcs USB 3.0 • 1 pcs USB 2.0
Supported hard drives:	2 x 8 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, P2P, ONVIF, Private
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast Simultaneous playback : • 1 Channel @ 8 Mpx • 1 Channel @ 5 Mpx • 2 Channels @ 4 Mpx • 2 Channels @ 3 Mpx • 4 Channels @ 1080p • 4 Channels @ 960p • 4 Channels @ 720p
Bitrate:	120 Mbps
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

ONVIF:	2.4
Mobile phones support:	Port no.: 6000 or access by a cloud (P2P) • Android: Free application BitVision , Android: Free application iVMS320 • iOS (iPhone): Free application BitVision , iOS: Free application iVMS320
Default IP address:	192.168.1.88
Default admin user / password:	admin / 12345
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 554
Alarm inputs / outputs:	—
PTZ control:	IP Speed Dome Cameras
Motion Detection:	Split the screen into zones : 24 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 4 A
Operation temp:	-10 °C ... 55 °C
Weight:	1.26 kg
Dimensions:	310 x 305 x 46 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Greek, Spanish, German, Portuguese, Russian, Turkish, Hungarian, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Top view:



Rear panel:



See how to mount a hard disk drive and configure the recorder:

:

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------