

Code: BNC-W/ZAC-RG59/PCT

COMPRESSION PLUG **BNC-W/ZAC-RG59/PCT**

Net: 1.06 EUR Gross: 1.06 EUR

Professional compression connector manufactured by American PCT company. The features of the connector have been specially matched to the RG-59 cables.

The connector is equipped with a plastic bush, which during compression of the connector is tightly pressed against the sheath of the cable (by putting on cone brass case - the compression ring). The dimensions are so matched that after compression connector is crimped on the cable sheath with a force so large that break the connector from the cable is impossible and so small that it does not damage the structure of the cable.



SPECIFICATION

Connector type:	BNC Straight plug
Attachment of connector elements:	Compression mounting
Shield fastening:	Compression mounting
Wire mounting:	Pressing
Application:	Coaxial cable
Cable diameter:	max. 5.9 mm
Impedance:	75 Ω
Material:	Brass (Nickel-plated)
Watertightness:	✓
Example of application:	RG59
Main features:	<ul style="list-style-type: none">• Wide frequency range• Watertightness of connector with cable connection• Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric• Properly compressed connection is highly resistant to break• Many patent-pending solutions• To crimp use the crimping tool ZAC/PCT / HT-5082R
Weight:	0.018 kg
Dimensions:	Ø 15 mm x 37 mm
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



OUR TESTS

The manual of proper prepare the end of the cable and compress of the BNC connector:



:

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------