

Code: MSP-300-R/IT

## WIRELESSLY TRIGGERED OUTDOOR SIREN **MSP-300-R/IT** SATEL

Net: **3 023.76 NOK** Gross: **3 023.76 NOK**

Outdoor, wirelessly triggered opto-acoustic siren designed to use in burglary and robbery signaling systems. Optical signaling source are LEDs, and acoustical signaling is generating by piezo transducer.

The device powered by the BAT-ER-3,6 powerful battery with a capacity of 13 Ah and a high temperature range.

High-impact polycarbonate enclosure, featuring a very high mechanical strength and guarantees aesthetic appearance of siren even after many years of using. Construction enables high level of tamper protection (against opening and removing from mounting surface).



### SPECIFICATION

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Support:                     | MTX-300                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Sound pressure level:        | 105 dB                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Main features:               | <ul style="list-style-type: none"><li>• Optical and acoustic signaling is triggered independently, by radio</li><li>• Tamper protection (detection of removing from mounting surface and enclosure opening)</li><li>• Remote configuration</li><li>• Selection of 4 different acoustic signals</li><li>• The advanced radio system ensures optimized communication with low current consumption</li><li>• Radio communication range (at open area) to 400 m</li></ul> |
| Color:                       | Red                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Power supply:                | Battery BAT-ER-3,6 (ER34615) 13 Ah                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Maximal current consumption: | 500 mA                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Backup time:                 | 3 years                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Operation temp:              | -40 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Weight:                      | 0.774 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Dimensions:                  | 148 x 254 x 64 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Manufacturer / Brand:        | SATEL                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Guarantee:                   | 2 years                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

### PRESENTATION

Internal view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Mounting side view:



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|

