

	SWITCHING ADAPTER 3.12V/1.2A/BL	SWITCHING ADAPTER 3.12V/2.5A/TAY	SWITCHING ADAPTER 3.12V/2A/BL USB	SWITCHING ADAPTER DRG-SU10W-1A2 Delta Electronics	POWER SUPPLY ADAPTER USB-C-W/230V/65W-GC	SWITCHING ADAPTER APS-053 SATEL	USB MAINS CHARGER SV2A/USB-C	POWER SUPPLY ADAPTER SV2A/1.35C1.5	POWER SUPPLY ADAPTER SV2A/5	POWER SUPPLY ADAPTER SV2A/5.5*PP200	USB MAINS CHARGER SV2A/USB-C	USB MAINS CHARGER SV2A/USB-C	USB MAINS CHARGER SV2A/USB-C-K	USB MAINS CHARGER SV2A/USB-W	USB CAR CHARGER SV/2.1A/2XUSB-QUICK3.0/CAR	USB MAINS CHARGER SV3A/USB-QUICK3.0/R STAZER	POWER SUPPLY ADAPTER SV2A/5	USB-C MAINS CHARGER CHAR07-GC Green Cell	USB MAINS CHARGER CHAR03-GC Green Cell	USB MAINS CHARGER CHAR03-GC Green Cell	USB MAINS CHARGER CHAR03-GC Green Cell	USB MAINS CHARGER CHAR03-GC Green Cell	USB CHARGER FX- USB-2A/B KEYSTONE	USB CHARGER FX-USB-C- PC/B KEYSTONE	USB MAINS CHARGER MCE-4798 MACLEAN ENERGY	USB CAR CHARGER POWER-RIDE/4W-GC Green Cell	POWER SUPPLY ADAPTER 6V/2A/4.0	POWER SUPPLY ADAPTER 9V/2A/5.5	POWER SUPPLY ADAPTER 9V/4A/5.5	SOLAR PANEL ESFP12 FOR THE IMOU C314 GO CAMERA		
																																
Power voltage	190.01 CZK 190.01 CZK	199.16 CZK 199.16 CZK	297.61 CZK 297.61 CZK	474.40 CZK 474.40 CZK	566.87 CZK 566.87 CZK	514.35 CZK 514.35 CZK	52.51 CZK 52.51 CZK	104.96 CZK 104.96 CZK	79.31 CZK 79.31 CZK	14270.33 CZK 14270.33 CZK	68.90 CZK 68.90 CZK	90.79 CZK 90.79 CZK	62.08 CZK 62.08 CZK	69.68 CZK 69.68 CZK	60.65 CZK 60.65 CZK	74.16 CZK 74.16 CZK	168.18 CZK 168.18 CZK	280.86 CZK 280.86 CZK	306.46 CZK 306.46 CZK	518.66 CZK 518.66 CZK	873.56 CZK 873.56 CZK	250.60 CZK 250.60 CZK	410.29 CZK 410.29 CZK	113.88 CZK 113.88 CZK	327.45 CZK 327.45 CZK	100.36 CZK 100.36 CZK	184.57 CZK 184.57 CZK	256.76 CZK 256.76 CZK	646.89 CZK 646.89 CZK			
In package	...	...	...	90 ... 264 V AC	...	195 ... 265 V AC	...	...	...	200 pcs The price for package	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Length of the cables	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	2.75 m	
Frequency range	...	...	...	...	...	50 Hz	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	50 / 60 Hz	...	
Model identifier	3.12V/1.2A/BL	3.12V/2.5A/TAY	3.12V/2A/BL	...	...	...	...	...	5V/2A/5.5	5V/2A/5.5*PP200	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	50 / 60 Hz	...	
Input voltage	100 ... 240 V AC	100 ... 240 V AC	100 ... 240 V AC	...	100 - 240 V AC	...	220 ... 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 ... 240 V AC	220 ... 240 V AC	100 ... 240 V AC	100 ... 240 V AC	12 ... 24 V DC	100 ... 240 V AC	100 - 240 V AC	100 ... 240 V AC	100 ... 240 V AC	100 ... 240 V AC	100 ... 240 V AC	100 ... 240 V AC	100 - 240 V AC	110 - 240 V AC	100 ... 240 V AC	12 ... 24 V DC	...	100 - 240 V AC	100 - 240 V AC	...	...	
Maximal load	...	...	...	1.5 A	...	0.5 A	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	4 A	...	
Output power	...	...	...	7.5 W	...	4 W	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	36 W	...	
AC input frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	...	50 / 60 Hz	...	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	...	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	...	50 / 60 Hz	50 / 60 Hz	...	...		
Vibration resistance	...	...	...	✓	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Output voltage	3.0 V, 4.5 V, 6.0 V, 7.5 V, 9.0 V, 12.0 V DC	3.0 V, 4.5 V, 6.0 V, 7.5 V, 9.0 V, 12.0 V DC	3.0 V, 4.5 V, 5.0 V, 6.0 V, 7.5 V, 9.0 V, 12.0 V DC	5 V DC	5 / 9 / 12 / 15 / 20 V DC	5 V DC, stabilized	5.0 V DC	5.0 V DC	5.0 V DC	5.0 V DC	5.0 V DC	5.0 V DC	5.0 V DC	5.0 V DC	...	5 / 9 / 12 V DC - 1 output, 5 V DC - 2 output	5 / 9 / 12 V DC	5.0 V DC	5 / 9 / 12 V DC	...	5 / 9 / 12 V DC - 1 output, 5 V DC - 2 output, 5 V DC - 3 outputs	5 / 9 / 12 V DC - 1 output, 5 V DC - 2 output, 5 V DC - 3 outputs	5 / 9 / 12 V DC - 1 output, 5 V DC - 2 output, 5 V DC - 3 outputs	5 / 9 / 12 V DC - 1 output, 5 V DC - 2 output, 5 V DC - 3 outputs	5 / 9 / 12 V DC - 1 output, 5 V DC - 2 output, 5 V DC - 3 outputs	5 / 9 / 12 V DC	6.0 V DC	9.0 V DC	9 V DC	6.2 V DC @ micro USB		
Average efficiency during work	...	...	...	...	...	...	...	78.7 %	78.7 %	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Efficiency at low load (10%)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Efficiency	...	...	...	> 76 %	...	≤ 72 %	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
No-load power consumption	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Operation temp. / Relative humidity	...	...	...	25 °C ... 71 °C / 5 ... 95 %	...	...	...	< 0.10 W	< 0.10 W	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Environment class	...	...	...	II	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Output current	max. 1.2 A	max. 2.5 A	max. 2.0 A @ DC, max. 1.2 A @ USB	...	3 / 3.25 A	...	1 A	2.0 A	2.0 A	2.0 A	2.0 A	2 A	2 A	2.0 A	...	3.1 / 1.8 / 1.8 A - 1 output, 3.1 A - 2 output	3 / 2 / 1.6 A	4.0 A	3 / 2 / 1.5 A	...	3 / 2 / 1.5 A - 1 output, 2.4 A - 2 output, 2.4 A - 3 output	3 / 2 / 1.5 A - 1 output, 2.4 A - 2 output, 2.4 A - 3 output	3 / 2 / 1.5 A - 1 output, 2.4 A - 2 output, 2.4 A - 3 output	3 / 2 / 1.5 A - 1 output, 2.4 A - 2 output, 2.4 A - 3 output	3 / 2 / 1.5 A - 1 output, 2.4 A - 2 output, 2.4 A - 3 output	3 / 2 / 1.5 A - 1 output, 2.4 A - 2 output, 2.4 A - 3 output	...	2.0 A	2.0 A	...	0.484 A	
Adapter type	Switching	Switching	Switching	Switching	...	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	...	
Operation temp	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Output voltage adjustment	✓	✓	✓	...	Automatic	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Number of outputs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	2 pcs	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Output power	15.0 W	30.0 W	30.0 W	...	15 / 27 / 36 / 45 / 65 W	...	5 W	10.0 W	10.0 W	10.0 W	10.0 W	10 W	10 W	10 W	21.6 W	19.2 W	20.0 W	max. 18 W	max. 30 W (total) max. 18 W - Port 1 max. 12 W - 2, 3 ports	max. 52 W (total) max. 18 W - Port 1 max. 12 W - 2, 5 ports	max. 65 W (total) max. 65 W - 1, 2 ports max. 18 W - Port 3	10 W	max. 20 W	18 W	max. 54 W (total), 18 W / Port USB	12.0 W	18.0 W	...	...	3 W		
Protections	Overvoltage	...	Overvoltage	• Overvoltage • Overload • Temperature	...	• Input : Short-circuit, DC filter to eliminate interferences • Output : Short-circuit, Overload	...	...	...	...	...	...	...	...	...	Multi-stage protection system for charging devices	Multi-stage protection system for charging devices	...	...	...	Thermal protection	Overload, Short-circuit, Overvoltage, Overheat	Overload, Short-circuit, Overvoltage, Overheat	Multi-stage protection system for charging devices	...	...	...	...	...	...		
Output	...	...	...	...	...	...	USB-A	Plug 1.35 / 3.5 mm - on the cable	Plug 2.1 / 5.5 mm on the cable	Plug 2.1 / 5.5 mm on the cable	USB-A	USB-A	USB-C	USB-A	2 x USB-A (1 x Quick Charge 3.0, 1 x 3.1 A)	USB-A	Plug 2.1 / 5.5 mm on the cable	USB-C - Quick Charge 3.0	3 x USB-A (1 x Quick Charge 3.0, 2 x 2.4 A)	5 x USB-A (1 x Quick Charge 3.0, 4 x 2.4 A)	2 x USB-C - PD3.0, 1 x USB-A - Quick Charge 3.0	USB-A	USB-C	3 x USB-A (1 x Quick Charge 3.0, 2 x 2.1 A)	3 x USB-A - Quick Charge 3.0	Plug 1.7 / 4.0 mm on the cable	Plug 2.1 / 5.5 mm on the cable	2.1/5.5 mm plug - on the cable	...			
Power connectors type	• AC : 230 V CEE 7/16 • DC - Angular plug : Replaceable plug tips - 7 pcs (2.5/0.7mm, 3.0/1.0mm, 3.5/1.3mm, 4.0/1.7mm, 5.0/1.7mm, 5.5/2.1mm, 5.5/2.5mm) The possibility of changing the polarity by inserting the plug appropriately	• AC : 230 V CEE 7/16 • DC - Angular plug : Replaceable plug tips - 6 pcs (2.5/0.7mm, 3.5mm, 3.5/1.3mm, 4.0/1.7mm, 5.5/2.5mm) The possibility of changing the polarity by inserting the plug appropriately	• AC : 230 V CEE 7/16 • DC - Angular plug : Replaceable plug tips - 7 pcs (2.5/0.7mm, 3.0/1.0mm, 3.5/1.3mm, 4.0/1.7mm, 5.0/1.7mm, 5.5/2.1mm, 5.5/2.5mm) The possibility of changing the polarity by inserting the plug appropriately	...	...	• 230 V CEE 7/16 • USB-C plug	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Main features	...	...	...	...	Power Delivery Technology - 65 W	• IEC 38 compliance • Can be installed in a 60mm electrical box	...	...	...	...	...	...	...	...	...	• Advanced power management • Smart battery charging to extend battery lifetime • Quick Charge 3.0 - fast charging • Blue backlight	• Advanced power management • Smart battery charging to extend battery lifetime • Quick Charge 3.0 - fast charging	...	• Quick Charge 3.0 - fast charging	• Quick Charge 3.0 - fast charging • Power Delivery technology 65W - 65 W • Green Cell Ultra Charge • Simultaneous charging of 3 devices	• Quick Charge 3.0 - fast charging • Power Delivery technology 65W - 65 W • Green Cell Ultra Charge • Simultaneous charging of 3 devices	• Quick Charge 3.0 - fast charging • Power Delivery technology 65W - 65 W • Green Cell Ultra Charge • Simultaneous charging of 3 devices	...	fast charging	• Quick Charge 3.0 - fast charging • Simultaneous charging of 3 devices	• Green backlight • Advanced power management • Smart battery charging to extend battery lifetime • Quick Charge 3.0 - fast charging	...	...	...	...		
Length of the cable	1.2 m	0.65 m	1.2 m	...	...	...	...	...	...	...	...	...	...	...	90 cm	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Housing type	Casing with plug	Casing with plug	Casing with plug	DIN	Desktop	Plastic	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Color	...	...	...	...	...	White	...	...	...	...	Black	White	Black	White	Black	Black	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Weight	0.092 kg	0.092 kg	0.128 kg	0.06 kg	0.4 kg	0.036 kg	0.035 kg	0.06 kg	0.075 kg	0.075 kg	0.035 kg	0.06 kg	0.032 kg	0.034 kg	0.026 kg	0.034 kg	0.172 kg	0.08 kg	0.1 kg	0.19 kg												