

Code: TR-40VA/IT

AC POWER SUPPLY ADAPTER **TR-40VA/IT** SATEL

Net: **62.54 EUR** Gross: **62.54 EUR**



Single phase safety isolating transformer with short-circuit and thermal protection, is designed and made according to EN61558-2-6 norm.

The power adapter is intended to be used in installations, which according to the CE Directives require the use of safety isolating transformer. Transformer windings are isolated and sealed with polyurethane inside self-extinguishing housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current. Please pay attention for proper cooling conditions of the power adaptor during work!

SPECIFICATION

Adapter type:	Transforming
Power voltage:	230 ... 250 V AC
Frequency range:	47 ... 63 Hz
Output voltage:	16 V, 18 V AC
Maximal load:	2.22 A
EN norm:	EN61558-2-6
Test voltage between PRI/SEC:	AC 4kV RMS
Safety class:	II
Isolation class:	B (130°C)
"Index of Protection":	IP44
Output power:	40 VA
Application:	<ul style="list-style-type: none">• to alarm systems powering• to automatic systems• to low-voltage light installation powering
Output:	2 pcs
Weight:	1.01 kg
Dimensions:	124 x 72 x 67 mm
Manufacturer / Brand:	SATEL

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Guarantee:

2 years

PRESENTATION

Adapter connectors (after remove the cover):



Top view:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

