

Code: DRR-40N

REDUNDANT POWER ADAPTER **DRR-40N**

Net: **16.98 EUR** Gross: **16.98 EUR**

The DRR-40N device enables the connection of two power supply adaptors or batteries in parallel. In case of damage one of the power source, the second power source is activated, what ensures continuous work of the whole system.

It is recommended to use the identical power adaptors, and if the power adaptors are equipped with output voltage adjustment, they should be set at the same level.



SPECIFICATION

Number of power inputs:	2
Number of power outputs:	1
Power voltage:	24 ... 48 V DC
Maximal power supply current:	40 A
Maximal voltage drop:	0.65 V
Efficiency:	> 97 %
Operation temp:	-40 °C ... 80 °C
Filter built-in:	—
Weight:	0.47 kg
Dimensions:	50 x 121 x 122 mm
Guarantee:	5 years

PRESENTATION


Front panel:




Rear panel (DIN rail installation):



Side view:



Dimensions:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60