

Code: HN1-13V2-3W

IP CAMERA **HN1-13V2-3W** - 1.3 Mpx 3.6 mm HYBRO-NET

Net: **44.01 EUR** Gross: **44.01 EUR**

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1280x960. Very easy operation by Internet Explorer browser allows the users to convenient and remote support, and also remote management of the camera. Included camera software enables management and integrated monitoring of many network cameras. Its using allows to create large surveillance system.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/3 " Aptina AR0130 CMOS
Digital Image Processor:	Hisilicon 3518E
Matrix size:	1.3 Mpx
Resolution:	1280 x 960 - 1.3 Mpx 1280 x 720 - 720p 720 x 576 - D1
Lens:	3.6 mm, 3.0 Mpx
View angle:	• 67 ° (manufacturer data) • 80 ° (our tests result)
S/N ratio:	> 50 dB
Range of IR illumination:	20 m
Memory card slot:	—
Image compression method:	H.264
Alarm inputs / outputs:	—
Bitrate:	1024 ... 5120 kbps
Main stream frame rate:	max. 25 fps - 960p
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	RTSP, DHCP, DDNS, NTP, HTTP, NETIP
Audio:	—
WEB Server:	Built-in

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Max. number of on-line users:	10
ONVIF:	2.04 - port 8899
RS-485 interface:	—
Mobile phones support:	Port no.: 34567 or access by a cloud (P2P) • Android: Free application XMEye • iOS (iPhone): Free application XMEye
Main features:	• ICR - Movable InfraRed filter • D-WDR - Wide Dynamic Range • Possibility to change the resolution, quality and bit rate • BLC - Back Light Compensation • Image rotation and mirror • Configurable: brightness, contrast, saturation • F-DNR (Defog) - Reduction of image noise caused by precipitation • Day/Night mode - configurable • Motion Detection - 22 x 18 motion zones
Vandal-proof:	✓
Power supply:	12 V DC / 340 mA
Housing:	Dome - Metal
Color:	White
"Index of Protection":	IP66
Operation temp:	-20 °C ... 50 °C
Weight:	0.304 kg
Dimensions:	Ø 93 x 72 mm
Supported languages:	English, Arabic, Brazilian Portuguese, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, Finnish, French, Greek, Hebrew, Spanish, Japanese, Korean, German, Persian, Polish, Portuguese, Russian, Romanian, Thai, Turkish, Hungarian, Vietnamese, Italian
Manufacturer / Brand:	HYBRO-NET
Guarantee:	2 years

PRESENTATION


Camera is out from clamping ring:



Mounting side view:



See how you can power the camera in PoE standard:



1. SWITCH PoE
 2. POE-802.3AF/C
 3. IP Camera
 4. Ethernet
 5. Ethernet + PoE
- In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------