

Code: DC-3-TEST

CARBON MONOXIDE (CO) DETECTOR **DC-3-TEST** Virone

Net: **22.01 EUR** Gross: **22.01 EUR**

The device is designed for continuous monitoring of CO (carbon monoxide) concentration in the air as well as detection and alarming when the maximum safe concentration of this gas is exceeded.

Gas concentration above the threshold level triggers visual and audible alarm signals. Device should be mounted at a height of about 1.5-2.0 m above the floor.



SPECIFICATION

Detection:	Carbon Monoxide (CO)
Alarm signaling:	• Alarm siren • Blinking LED
Gas concentration to trigger alarm:	• 300 ppm for max. 3 mins • 100 ppm for 10 ... 40 minutes • 50 ppm for 60 ... 90 minutes • 30 ppm for >120 minutes
Battery power supply:	3 x battery LR6 (AA) (included)
Current consumption:	• 30 μA (Standby mode) • 65 mA (alarm)
Main features:	• Electrochemical carbon monoxide detector • Alarm signaling : low level (> 40 ppm) / high level • Range : 10 ... 550 ppm • LCD display • Alarm siren > 85 dB / 3 m • Test mode • Silent mode < 200 ppm • Low battery level alarm • Failure signaling • The memory of the last highest concentration of CO, which triggered the alarm • Detector lifetime : 10 years • EN 50291-1:2018 compliance
Operation temp:	-10 °C ... 45 °C
Weight:	0.20 kg
Dimensions:	110 x 77 x 36 mm
Manufacturer / Brand:	Virone

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------