

Code: MSD-300

WIRELESS SMOKE AND HEAT DETECTOR **MSD-300** SATEL

Net: **38.71 EUR** Gross: **38.71 EUR**

Smoke and heat detector allows to early detection of a developing fire. Besides sending the information to the control panel, the MSD-300 detector can warn of the danger of using the built sound alarm.



SPECIFICATION

Detection:	smoke, heat
Alarm signaling:	• Buzzer • Blinking LED • Signal to control panel
Frequency band:	433.05 ... 434.79 MHz
Radio communication range (at open area):	to 200 m
Battery:	CR123A 3 V
Backup time:	~ 3 years
Current consumption at standby mode:	50 µA
Maximal current consumption:	20 mA
Class according to EN 54-5 (thermal sensor):	A1R
Minimal static temperature of alarm notification:	54 °C
Maximal static temperature of alarm notification:	65 °C
Operation temp:	0 °C ... 55 °C
Weight:	0.17 kg
Dimensions:	Ø 108 x 61 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

View after remove the cover:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------