

Code: STPV-1

VIDEO TESTER STPV-1

Net: 232.90 EUR Gross: 232.90 EUR

Universal CCTV tester with many functions useful for CCTV systems, network (twisted-pair) installations and fiber optic installations (optical power meter).



SPECIFICATION

Video standard:	PAL/NTSC
Display:	3.5 " TFT LCD 960x240
Video input:	1 pcs BNC
Video output:	1 pcs BNC
Video signal level meter:	mV (for PAL) IRE (for NTSC)
Video signal generator:	Eight color-bars generating in multi-tv-system modes
Serial ports:	RS-232, RS422 simplex, RS-485
Protocols:	Support for over 20 RS485 protocols Pelco-P, Pelco-D, SAMSUNG, PANASONIC, LILIN, YAAN
Baud rates:	150, 300, 600, 1200, 2400, 4800, 9600, 19200 bps
LAN (twisted-pair) or telephone cables testing:	UTP cables or phone lines connecting test with RJ-45 connectors
RS-485, RS-422, RS-232 lines testing:	Data analysis from control device (the commands are displayed in hexadecimal)
Digital multimeter:	Measurement voltage, current, resistance, capacitance, continuity test, diode test
Audio test:	Preamplifier and speaker built-in (JACK 3.5 mm socket)
Operation as power source:	12 V DC / 1 A (real value: DC 11.5V / 750mA)
Optical power measurement:	Optical power measurement in fiber optic networks (ST and SC adapters)
Operation:	OSD
Power supply:	5 V DC (power adapter included) / battery 3.7V / 3000mAh (LiPo)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Estimated battery operation time:	12 hours (after 3-4 h charging time)
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	30 % ... 90 %
Main features:	<ul style="list-style-type: none"> • Video signal test • Test signal generator • Motor units and PTZ (Speed Dome) cameras control • LAN (twisted-pair) cables testing • Data monitor - serial port data analysis (RS-485 or RS-232) • PTZ address scanning - searching of the PTZ addresses • Digital Multimeter • Optical power meter • Audio test • DC 12V / 1A power source
Weight:	0.52 kg
Dimensions:	176 x 94 x 36 mm
Supported languages:	English, French, Spanish
Guarantee:	2 years

PRESENTATION

Front panel (control video signal generator is on):



Sides view:



Top view:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



The device is protected by a rubber cover:



In the kit:



The tester with accessories housed in a handy bag:



OUR OPINIONS



- You don't need to take the monitor, PTZ control keyboard, video signal generator, digital multimeter, etc.
- Everything you need to work is the compact, small, universal device.
- Perfect to build and create the CCTV system.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------