



	<a href="#">CABLE PAIR DETECTOR WITH RJ-45 CABLE TESTER UT-682 UNI-T</a>	<a href="#">SWITCHING ADAPTER MDR-40-48 MEAN WELL</a>
		
	29.43 EUR 29.43 EUR	30.37 EUR 30.37 EUR
Adapter type	...	Switching
Tested cables	UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C)	...
Power voltage	...	85 ... 264 V AC / 120 ... 370 V DC
Output voltage	...	48 V DC
Output voltage adjustment	...	48 ... 56 V
Voltage tolerance	...	± 1 %
Maximal load	...	0.83 A
Output power	...	39.8 W
Number of outputs	...	2 pcs
Main features	<ul style="list-style-type: none"> <li>• Test for the presence of a short circuit, open circuit</li> <li>• Polarity indicator for telephone wire pairs : ± (5V ... 52V)</li> <li>• The maximum length of the telephone line : 3000 m</li> <li>• Optical - sound signaling</li> <li>• Low battery indicator</li> </ul>	...
Efficiency	...	88 %
Housing type	...	DIN
Power supply	2 x 9V, type 6F22 battery (included)	...
MTBF (Mean Time Between Faults)	...	min. 301700 hours
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	20 % ... 75 %	...
Vibration resistance	...	IEC60068-2-6, 10 ... 500 Hz max. 2 G
Protections	...	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overvoltage</li> <li>• Overload protection</li> </ul>
Operation temp. / Relative humidity	...	-20 °C ... 70 °C / 20 % ... 95 %
Weight	<ul style="list-style-type: none"> <li>• 0.11 kg - Transmitter</li> <li>• 0.14 kg - Receiver</li> </ul>	0.26 kg

Dimensions	• 125 x 48 x 29 mm - Transmitter • 194 x 50 x 30 - Receiver	40 x 100 x 90 mm
Manufacturer / Brand	UNI-T	MEAN WELL
Guarantee	2 years	3 years