



	PLUG F/5.2-CFS	ACCESS CONTROL PANEL ACCO-NT2 SATEL
		
	0.57 AUD 0.57 AUD	605.61 AUD 605.61 AUD
Connector type	"F" Straight plug	...
Attachment of connector elements	Twisted-on	...
Shield fastening	Twisting-on	...
Inputs	...	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264
Wire mounting	—	...
Application	Coaxial cable	...
Cable diameter	max. 5.2 mm	...
Impedance	75 Ω	...
Outputs	...	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264
Material	Metal	...
Communication	...	<ul style="list-style-type: none"> • 2 x RS-485 • Expander bus - up to 32 expander modules
Events memory	...	<ul style="list-style-type: none"> • Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel, • Max. 100 000 events read from each access control module
Users + admins	...	<ul style="list-style-type: none"> • 8000 + 1 • Max. 65 000 users in the whole ACCO NET system
Output load	...	<ul style="list-style-type: none"> • OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC

Main features	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance 	<ul style="list-style-type: none"> • Support for up to 255 access control modules • Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition) • Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway) • Ability to block/unblock partition at a specified time, or as per access schedule, • Ability to assign 4 identifiers and a keyfob to a single user, • Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user, • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Ability to control the control panel outputs by using keyfobs • Implementation of logic functions on inputs and outputs • Support for turnstiles • Electrical protection of all inputs and outputs as well as communication buses
Power supply	...	12 V DC / 140 mA (max)
Battery backup support	...	—
Operation temp	...	-10 °C ... 55 °C
Permissible relative humidity	...	93 % (non-condensing)
Weight	0.005 kg	0.096 kg
Dimensions	Ø 11 mm x 20 mm	151 x 69 x 17 mm
Manufacturer / Brand	...	SATEL
Guarantee	2 years	2 years