






	IP CAMERA IPC-HFW1430DT-STW-0280B Wi-Fi - 4 Mpx 2.8 mm DAHUA	ELECTRIC CABLE YDY-5X4.0	ALKALINE BATTERY BATT LR20-MAXPLUS*P2 1.5 V LR20 (D) ENERGIZER	STRAIGHT CABLE DUCTING LE-638130 24x14 LEGRAND	CHALK LINE REEL ST-0-47-100 STANLEY
					
	157.45 EUR 157.45 EUR	4.84 EUR 4.84 EUR	4.09 EUR 4.09 EUR	2.06 EUR 2.06 EUR	11.00 EUR 11.00 EUR
Line length	30 m
Standard	IP
Width	24 mm	...
Height	14 mm	...
Length	2000 mm	...
Application	<ul style="list-style-type: none"> • For use in masonry work, • Electrical works, such as marking lines for pipes, trays or lines for lighting lamps
In package	2 pcs The price for package
Material	PVC	...
In section	...	100 m . Price for 1m when buying a whole roll
Operation temp	15 °C ... 60 °C	...
Inner conductor	...	5 x 4.0 mm ² - Cu wire
Type (size)	AM1 / LR20 (D)
Rated voltage	...	450 / 750 V	1.5 V
Outer coating	...	Ø 14.5 mm - PVC
Coating color	...	White
Main features	<ul style="list-style-type: none"> • Longest Lasting Alkaline Batteries, • Powerful and high performance, • Holds power for up to 10 years of shelf life, • Leak-proof construction 	...	<ul style="list-style-type: none"> • Universal hook at the end of the line • Can be used as a vertical • A container for chalk powder
Resolution	2560 x 1440 - 4 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Sensor	1/3 " Progressive Scan CMOS
Lens	2.8 mm
View angle	90 °
Range of IR illumination	30 m
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	H.265+ / H.265 / H.264+ / H.264
Alarm inputs / outputs	—
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support, • Audio detection, • Audio transmission via network
Main stream frame rate	20 fps @ 4 Mpx 25 fps @ 3 Mpx
Interface	<ul style="list-style-type: none"> • Wi-Fi - 2.4 GHz IEEE 802.11 b/g/n, • 10/100 Base-T (RJ-45)
WEB Server	Built-in
ONVIF	✓
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	DHCP
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777
Port ONVIF	80
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Wi-Fi Module, Range : 80 m (open area) • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - configurable Back Light Compensation • Auto White Balance • AGC - Automatic Gain Control • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image • Motion Detection - max. 4 zones - Human detection
Power supply	12 V DC / 350 mA (power adapter included)
Power consumption	≤ 4.1 W
Housing	Compact - Plastic	Aluminum, Waterproof
Color	White	White	...
"Index of Protection"	IP67	IP40	...
Mechanical protection class	—
Operation temp	-30 °C ... 50 °C
Weight	0.35 kg	...	0.132 kg	0.20 kg	0.3 kg
Dimensions	180 x 83 x 115 mm	120 x 75 x 44 mm
Supported languages	Polish . English, Russian
Manufacturer / Brand	DAHUA	...	ENERGIZER	LEGRAND	STANLEY
Guarantee	3 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00