




	THERMALLY CONDUCTIVE PASTE AG-EXTREME/3G 3 g AG TERMOPASTY	ACCESS POINT RBL41G-2AXD hAP ax lite Wi-Fi 6 2.4 GHz 574 Mbps MIKROTIK	CONTACTS CLEANING PREPARATION KONTAKT-S/400 SPRAY 400 ml AG TERMOPASTY
			
	6.47 EUR 6.47 EUR	62.36 EUR 62.36 EUR	6.69 EUR 6.69 EUR
Frequency range	...	2.4 GHz	...
Package	Syringe 3 g	...	Spray 400 ml
Antenna type	...	2 x Internal antenna	...
Thermal conductivity	> 6 W/(m·K)
Application	Cleaning and regeneration of contacts
Standards	...	IEEE 802.11ax/n/b/g	...
Baud rates	...	574 Mbps	...
Thermal impedance	< 0.004 °C-in ² /W
Color	Gray
LAN ports	...	3 x 10 / 100 / 1000 Mbps LAN 1 x 10 / 100 / 1000 Mbps Uplink	...
LED indicators	...	Power, User, 3 x Ethernet, WAN	...
Receiver sensitivity	...	<ul style="list-style-type: none"> • 1M : -100 dBm • 11M : -100 dBm • 6M : -95 dBm • 54M : -77 dBm • MCS0 : -95 • MCS7 : -75 • MCS9 : -69 dBm • MCS11 : -61 dBm 	...
DDNS	...	✓	...
DHCP server	...	✓	...
Firmware update	...	✓	...
Operating system	...	MikroTik RouterOS	...
Management interface	...	Web browser	...
Transmitter power	...	max. 22 dBm	...
Power supply	...	• 5 V DC / 2.4 A (power adapter included)	...
Main features	The set includes an applicator for easy application of the paste to the surface	<ul style="list-style-type: none"> • Wi-Fi 6 • Built-in 4-port switch • Port USB • Mode button 	Spray preparation with a brush for easy application in hard-to-reach places

Operation temp	<ul style="list-style-type: none"> • -50 °C ... 250 °C (continuous operation) • -40 °C ... 340 °C (instantaneous operation) 	-40 °C ... 70 °C	...
Weight	...	0.22 kg	0.36 kg
Dimensions	...	124 x 96 x 53 mm	Ø 66 x 187 mm
Manufacturer / Brand	AG TERMOPASTY	MikroTik	AG TERMOPASTY
Guarantee	2 years	2 years	...