



	AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA DS-2CE57H0T-VPITF(2.8mm)(C) - 5 Mpx Hikvision	WIRELESS DOORBELL WDP-12A3 EURA
		
	87.03 EUR 87.03 EUR	11.77 EUR 11.77 EUR
Signaling mode	...	Optical - sound signaling
Number of ring-tones	...	32
Standard	AHD / HD-CVI / HD-TVI / CVBS	...
Volume adjustment	...	—
Operation range	...	max. 50 m in open area
Sensor	Progressive Scan CMOS	...
Frequency band	...	433.92 MHz
Matrix size	5 Mpx	...
Transmitter power	...	< 5 mW
Battery power supply	...	<ul style="list-style-type: none"> • Battery CR2032 3V (included) - Doorbell button, • 2 x Battery 1.5 V LR6 (AA) (not included) - Wireless doorbell
Main features	...	<ul style="list-style-type: none"> • The number of connected doorbells and cooperated buttons can be increased as required • Volume max. 80 dB / 1 m • Low power consumption
Resolution	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI • 1920 x 1080 - 1080p @ HD-TVI • 960 x 576 - 960H @ PAL 	...
Range of IR illumination	20 m	...
IR illuminator power adjustment	Automatic	...
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> • 85 ° (manufacturer data) • 79 ° (our tests result) 	...
Operation temp	...	<ul style="list-style-type: none"> • -10 °C ... 35 °C Doorbell button, • 0 °C ... 35 °C Wireless doorbell
IR illuminator support	ICR - Movable InfraRed filter	...

Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Main features	<ul style="list-style-type: none"> • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • D-WDR - Wide Dynamic Range • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines 	...
OSD menu	✓	...
Power supply	12 V DC / 340 mA	...
Power consumption	≤ 4.3 W	...
Housing	Dome, Metal	...
"Index of Protection"	IP67	<ul style="list-style-type: none"> • IP44 - Doorbell button • IP20 - Wireless doorbell
Vandal-proof	IK10	...
Color	White	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.37 kg	<ul style="list-style-type: none"> • 0.034 kg - Doorbell button • 0.058 kg - Wireless doorbell
Dimensions	Ø 111 x 85 mm	<ul style="list-style-type: none"> • 38 x 81 x 23 mm - Doorbell button • 64 x 78 x 32 mm - Wireless doorbell
Manufacturer / Brand	Hikvision	EURA
SAP Code	300613629	...
Guarantee	3 years	2 years