



	IP SPEED DOME CAMERA OUTDOOR IPC6612SRX25-VG LightHunter - 1080p 5...125 mm UNIVIEW	SOFTWARE RCMP4-1000 ROGEB
		
	1138.40 EUR 1138.40 EUR	3936.15 EUR 3936.15 EUR
License	...	RCP Master 4
Standard	TCP/IP	...
Number of employees	...	max. 1000
Number of workstations	...	1
Sensor	1/2.8" Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Resolution	1920 x 1080 - 1080p , 1280 x 960 1.3 Mpx , 1280 x 720 720p	...
Lens	5 ... 125 mm	...
View angle	54 ° ... 2.6 °	...
Optical zoom	x 25	...
Digital zoom	—	...
Range of IR illumination	150 m	...
Video output	—	...
Preset rotation speed	• 180 °/s (horizontal) • 80 °/s (vertical)	...
Rotation speed (manual control)	• 2 °/s ... 75 °/s (horizontal) • 2 °/s ... 75 °/s (vertical)	...
Horizontal rotation range	360 ° - continuous	...
Vertical rotation range	-15 ° ... 90 °	...
RS-485 interface	✓	...
Number of presets	1024	...
Horizontal scan	✓	...
Route settings	16	...
Supported operating systems	...	Windows
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	2 / 1	...
Audio	• External microphone input • Audio output • Bi-directional audio streaming support • Audio detection	...
Main stream frame rate	25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Mobile phones support	Port 37777 • Android: Free application EZView • iOS (iPhone): Free application EZView	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...

<p>Main features</p>	<ul style="list-style-type: none"> • Intelligent Object Tracking • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • Configurable Privacy Zones - 24 • Motion Detection • Tamper signaling • Image rotation and mirror • Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions • Overvoltage protection : 6 kV • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area 	<ul style="list-style-type: none"> • Export to personnel and payroll programs • Configuration and T&A events importing possibility from RACS 4 and RACS 5 access control systems • Data exchange (users, T&A modes and events) on database level with RACS 5 system • Optional automatic assignment of daily working time in case of on-duty leave • Serial operations (absences, leave limits) • Definition of holidays and report on their usage • Individual work time calendars with the possibility to correct calendars for particular employees (e.g. working in different time, changeover, etc.) • Possibility to define standard and non-standard work time, support for multi-shift working system • Support for paid/unpaid breaks and overtime (10 predefined types) • Possibility to create any composition of reports, both cumulative for employee group and individual for particular employees • Report Wizard for creating custom reports according to user requirements • Custom reports templates wizard • Report exporting in such formats as Adobe Acrobat (.pdf), Microsoft Excel (.xls) and Rich Text Format (.rtf) • Possibility to define operator accounts for management of particular groups of employees • MS SQL CE or MS SQL Server database types • Possibility of operation with database from third party software (own implementation of T&A events inserting by external system) • Free of charge updates within the same versions of software • Definition of access granting types, calendars, attendance and absence types, maximal and minimal attendance times (e.g. maximal daily break of particular type) • Additional options related to late comings, early leavings, rounding the time for work start and end, inclusion of time before and after standard working hours, etc. • Possibility to correct and insert missing T&A events and to modify absences <p><u>New features in RCP Master 4:</u></p> <ul style="list-style-type: none"> • Operation in a web browser (as part of the RCP Master 4 Web application) • Continuous calendars • Defining patterns of calendars • Hourly absences • Management of holiday requests • Accepting and rejecting events • Annual record sheet of working time • The ability to create your own types of overtime • Skipping intermediate events • Rounding off calculated times • Service entrance with automatic opening of the day • Automatic counting of overtime during the night hours • Flag about non-performance of the standard within days • An offset of the first entry and the last exit
----------------------	--	--



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power supply	<ul style="list-style-type: none"> • PoE (802.3at). • 12 V DC / 3 A (power adapter included) 	...
Power consumption	max. 25 W	...
Housing	Speed Dome, Metal + Plastic	...
Color	White + Black	...
Operation temp	-40 °C ... 65 °C	...
"Index of Protection"	IP66	...
Vandal-proof	—	...
Weight	3.5 kg	...
Dimensions	Ø 220 x 370 mm	...
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian	English, Polish
Manufacturer / Brand	UNIVIEW	ROGER
Guarantee	2 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00