









	KRONE BACK-MOUNT FRAME 1.5A-GN-10/10	ASSEMBLY FOOT LPCB-I	ACCESS CONTROLLER ASC2102B-T DAHUA	WIRELESS VIDEO DOORBELL ATLO-DBC1-TUYA Wi-Fi, Tuya Smart	LED STRIP CABLE AD-TL-6498/RGBW/25M 25 m ORNO	ACCESS CONTROLLER ASC3202B DAHUA	WIRELESS DOOR CHIME ATLO-DB-TUYA	SLEEVE AND EXPANSION ANCHORS KM-M10X80-PA
								
	7.57 EUR 7.57 EUR	0.10 EUR 0.10 EUR	175.87 EUR 175.87 EUR	31.90 EUR 31.90 EUR	17.41 EUR 17.41 EUR	504.82 EUR 504.82 EUR	5.89 EUR 5.89 EUR	1.16 EUR 1.16 EUR
Number of mounted profile modules	10 pcs
Number of served transitions	2 (two-way)	2
Length of the cable	25 m
Signaling mode	Optical - sound signaling	...
Sensor	Progressive Scan CMOS - 2 Mpx
Type of mounted profile modules	10PAR
Number of ring-tones	52	...
Support	DAHUA ASC2204C-H	Cooperation with the access control systems
Resolution	1920 x 1080 px - 1080p
Assembly	...	• Mounting to the PCB - M3 screw • Mounting to the ground - M4 screw
In package	4 pcs The price for package
Lens	2.5 mm
Number of supported readers	4 pcs	• 2 pcs RS-485, • 2 pcs Wiegand
Volume adjustment	4 volume levels, 10 ... 90 dB	...
Battery backup support	—	—
Screw	M10 x 80 mm
Operation range	80 m - in open area	...
Output lines	5 pcs - Relay
Inner conductor	5 x Ø 0.35 mm - Stranded wire
Drilling diameter	14 mm
View angle	• 135 ° (manufacturer data) • 101 ° (our tests result)
Alarm inputs / outputs	5 / 1	2 / 2
Screw threading length	36 mm
Frequency band	433.92 MHz ± 0.2	...
IR illuminator	10 m
Sleeve diameter	13.5 mm
Sleeve length	53 mm
LED illuminator	—
Material	Steel galvanized
Wireless transmission range	The range limited only by the availability of the Wi-Fi network
Outer coating	5 x Ø 1.6 mm - PVC
Wi-Fi standard	IEEE 802.11 b/g/n : 2.4 GHz
Application	LED strips - RGBW	Concrete, Solid clay brick
Network interface	Wi-Fi : 2.4 GHz
Communication	• RS-485, • Wiegand 34/26, • Control panel CAN (Controller Area Network)	• 3 x RS-485, • 2 x Wiegand 34/26, • 1 x Ethernet 10 / 100 Mbps (RJ-45)
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS
Coating color	Black + Green + Red + Blue + White
Image compression method	H.264 / MJPEG / JPEG
Network protocols	P2P, IPv4, DNS, DDNS, TCP, UDP, ONVIF CGI
Operation modes	• Main control mode • Sub control mode

Main features	<ul style="list-style-type: none"> • Micro SD memory cards up to 128GB support (possible local recording). • PIR detector - Motion Detection, Detector range 3 m, • loitering detection • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network : WiFi, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging • Increased battery life • Low current consumption • Operating frequency - Wireless doorbell : 433 MHz
Mount	Surface-mounted
Main features	<ul style="list-style-type: none"> • 20 000 indexed users • History of 30 000 events • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Door Left Open and Door Forced Open alarms • Watchdog built-in • Possibility to mount on a wall, or on the DIN TS-35 rail 	For indoor use	<ul style="list-style-type: none"> • Support for 2 doors (2x door sensor, 2x exit button, 2x alarm line, 2x lock control) • 1000 indexed users • Support up to 3000 finger prints • Memory of 5000 RFID cards • Support storage of 300 000 records • 128 General Purpose Schedules • Identification modes : RFID card, remote access, PIN, Fingerprint - Any combination of the above • Tamper protections • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Beep signal - Buzzer • White list, Black list • Web-Server built-in • Software update via network • Monitoring and configuration through network - SmartPSS Lite application • Power output 12 V DC / 1 A - supplying power to the lock • Support hardware I/O port configuration and export configuration diagrams • ONVIF compliance 	<ul style="list-style-type: none"> • Low power consumption • Receiver sensitivity : -110 dBm • Simple and quick device installation 		
Power supply	12 V DC / 1 A	<ul style="list-style-type: none"> • 2 x 18650 battery 3.7 V / 2600 mAh (not included) • 5 V DC - Charging via micro USB port (cable included) 	...	<ul style="list-style-type: none"> • 12 V DC / 2.5 A • PoE (802.3at) 	100 ... 240 V AC	...
Power consumption	<ul style="list-style-type: none"> • ≤ 2 W (standby) • max. 20.4 W @ 12 V (operation) • max. 14.4 W @ PoE (operation) 	≤ 0.5 W	...
"Index of Protection"	IP66
Housing	Waterproof - Plastic	...	Plastic (PC + ABS)	Plastic	...
Color	White / Black	...	White	White	...
IK rating	IK06
Operation temp	-30 °C ... 60 °C	...	-10 °C ... 55 °C
Permissible relative humidity	max. 95 % (non-condensing)	...	5 % ... 95 % (non-condensing)
Weight	...	0.001 kg	0.384 kg	<ul style="list-style-type: none"> • 0.084 kg - Wireless Video Doorbell • 0.028 kg - mounting base 	...	0.72 kg	0.06 kg	...
Manufacturer / Brand	...	DELTA	DAHUA	...	ORNO	DAHUA
Dimensions	225 x 112 x 50 mm	20.2 x 20.5 x 9.3 mm	209 x 117 x 51 mm	<ul style="list-style-type: none"> • 142 x 46 x 32 mm - Wireless Video Doorbell • 158 x 62 x 17 mm - mounting base 	...	186 x 186 x 58 mm	82 x 82 x 65 mm	...
Guarantee	2 years	3 years	3 years	2 years	2 years	3 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00