


	<a href="#">WIRELESS PIR CEILING DETECTOR AX PRO DS-PDCL12-EG2-WE Hikvision</a>	<a href="#">EXTENDER EXT-POE4 PULSAR</a>
		
	255.00 PLN 255.00 PLN	107.00 PLN 107.00 PLN
Support	HIKVISION AX PRO	...
Application	Indoor	...
Input voltage	...	42 ... 57 V DC
Pyroelectric sensor	quadruple	...
Output voltage	...	42 ... 57 V DC
Sensor type	Passive Infra Red (PIR)	...
Number of inputs	...	1
Number of outputs	...	2
Connector	...	3 x RJ-45 socket
LED indicators	...	Link/Act
Range	max. 12 m / 360 ° from a height 2.4 m area Ø 8 m from a height 4 m area Ø 12 m	...
Sensitivity adjustment	Auto, low level	...
Recommended installation height	2.4 m ... 4 m	...
Supported data rates	...	<ul style="list-style-type: none"> <li>• Range : 100 m - Input, 100 m - 2 x Output,</li> <li>• Supported data rates 10 / 100 Mbps - Fast Ethernet</li> </ul>
Frequency range	868 MHz - Tri-X Wireless	...
Radio communication range (at open area)	max. 1600 m	...
Output power	...	max. 14.4 W / port PoE , max. 20 W (total)
Alarm signaling	<ul style="list-style-type: none"> <li>• LED indicator : Color - blue,</li> <li>• Signal to control panel</li> </ul>	...
Protections	...	<ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Overload</li> <li>• Short-circuit</li> </ul>
Autodiagnosics	—	...
Housing	...	Metal
Prealarm feature	—	...
Pet immunity	—	...

Operation temp. / Relative humidity	...	-10 ... 40 °C / 10 ... 90 %
Digital temperature compensation	✓	...
Target speed range	0.3 ... 2 m/s	...
Main features	<ul style="list-style-type: none"> <li>• SEC (Smart Environmental Control) - advanced digital signal processing and 3D optics</li> <li>• Signal indicator</li> <li>• Bidirectional communication</li> <li>• AES-128 data encryption</li> <li>• Frequency hopping against jamming for reliable transmission</li> <li>• Tamper detection - opening the enclosure, removing from mounting surface</li> <li>• Remote management</li> </ul>	...
Power supply	1 x battery CR123A 3 V (included)	...
Backup time	~ 5 years	...
Current consumption	max. 81 mA	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.108 kg	0.10 kg
Dimensions	Ø 101 x 33 mm	86 x 77 x 26 mm
Manufacturer / Brand	Hikvision	PULSAR
SAP Code	314300159	...
Guarantee	2 years	2 years

