

	LED LIGHTING CONTROLLER WITH REMOTE CONTROL LED- RGB-WC/RF 2.4 GHz, RGB 12 ... 24 V DC MiBOXER/ Mi-Light	SWITCH POE APTI- POE0802G-120W-ECO 8- PORT	ACCESS CONTROL PANEL ACCO-NT2 SATEL
			
	17.28 EUR 17.28 EUR	46.22 EUR 46.22 EUR	375.10 EUR 375.10 EUR
Application	Works with LED lighting - (RGB) 12-24V LED strips
Inputs	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264
Rated voltage	12 ... 24 V DC
LAN ports	...	<ul style="list-style-type: none"> • 8 x RJ45 10/100 Base-TX (8 x PoE (802.3af/at)), • 2 x RJ45 100/1000 Base-TX - Uplink 	...
Outputs	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264
Maximal total load	<ul style="list-style-type: none"> • 120 W @ 12 V, • 240 W @ 24 V
Communication	<ul style="list-style-type: none"> • 2 x RS-485 • Expander bus - up to 32 expander modules
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 Mbps : 8 x Port LAN & PoE, • 100 / 1000 Mbps : 2 x Port RJ45 (Uplink) 	...
Total maximal current	6 A / Channel, 10 A (total)
Number of inputs	1
Number of outputs	4 (power)
Maximal output power	...	30 W / port PoE - 1 ... 8 ports	...
Events memory	<ul style="list-style-type: none"> • Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel, • Max. 100 000 events read from each access control module
Maximal total power	...	120 W	...
MAC addresses table	...	2k	...
Users + admins	<ul style="list-style-type: none"> • 8000 + 1 • Max. 65 000 users in the whole ACCO NET system

Management	...	—	...
Connector type	• screw terminals, • 5.5/2.1 socket / screw terminals - power input
Wireless	2.4 GHz
Radio communication range (at open area)	30 m
Mobile phones support	—
Operation modes	...	E+V - Extend On : 250 m @ 10 Mbps - 1 ... 4 ports	...
Output load	• OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC
LED diodes	...	Power, Extend, Link/Act, PoE	...
Color	White
Certificates	...	CE	...
Housing	Plastic	Metal	...
Main features	<ul style="list-style-type: none"> • The repeater function allows you to transfer control to subsequent LED-W-WC / LED-RGB-WC / LED-RGBW-WC modules even beyond the direct range of the remote control, • The set includes a 2.4 GHz radio remote control to control the controller, • Remote control power supply: 2x AAA 1.5V batteries (not included) 	<ul style="list-style-type: none"> • Power supply PoE, Endspan mode support : 1-2(+), 3-6(-) • EXTEND mode - 1 ... 4 ports • Port PoE Priority • Auto-learning and Auto-aging functions support for MAC addresses • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Mounts for mounting the device in the RACK 10" system 	<ul style="list-style-type: none"> • Support for up to 255 access control modules • Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition) • Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway) • Ability to block/unblock partition at a specified time, or as per access schedule, • Ability to assign 4 identifiers and a keyfob to a single user, • Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user, • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Ability to control the control panel outputs by using keyfobs • Implementation of logic functions on inputs and outputs • Support for turnstiles • Electrical protection of all inputs and outputs as well as communication buses

Power supply	...	110 ... 240 V AC, 50 / 60 Hz	12 V DC / 140 mA (max)
Battery backup support	—
Operation temp	-10 °C ... 40 °C	-10 °C ... 55 °C	-10 °C ... 55 °C
Permissible relative humidity	93 % (non-condensing)
Weight	0.05 kg	0.68 kg	0.096 kg
Dimensions	85 x 45 x 22 mm	200 x 122 x 45 mm	151 x 69 x 17 mm
Manufacturer / Brand	MiBOXER / Mi-Light	APTI	SATEL
Guarantee	2 years	2 years	2 years