



	POLE MOUNT USP-SUN-340 FOR SOLAR PANELS	UPS AT-UPS3000RT/2-RACK 3000 VA EAST
		
	148.80 EUR 148.80 EUR	865.80 EUR 865.80 EUR
Material	Aluminum	...
Power adapter type	...	Online
Nominal power	...	2700 W
Tilt angle adjustment:	✓	...
Apparent Power	...	3000 VA
Maximum pole diameter	115 mm	...
Mounting profile length	1200 mm	...
Input voltage	...	230 V AC \pm 25 %
Input frequency	...	50 / 60 Hz (auto detection)
Output voltage	...	230 V AC \pm 5 % (Pure Sine Wave)
Output frequency	...	50 / 60 Hz
Voltage adjustment	...	\pm 1 %
Frequency adjustment	...	—
Transfer time	...	4 ms
Charging time (recover to 90% capacity)	...	8 hours
Battery	...	8 x 12V/9Ah
Estimated battery operation time	...	<ul style="list-style-type: none"> • 120 minutes @ 200 W, • 60 minutes @ 400 W, • 40 minutes @ 600 W, • 25 minutes @ 800 W, • 20 minutes @ 1000 W, • 12.5 minutes @ 1200 W, • 9 minutes @ 1600 W, • 7.5 minutes @ 1800 W, • 6.5 minutes @ 2000 W, • 5 minutes @ 2400 W, • 4 minutes @ 2700 W
Number of outputs	...	<ul style="list-style-type: none"> • 1 pcs CEE 7/3 (Schuko), • 2 pcs IEC-320 C13
Management software	...	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)
Protections	...	<ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • EPO (Emergency power off) switch • Ethernet filter

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation state indication	...	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, • Sound signaling
Main features	<ul style="list-style-type: none"> • Maximum power of the mounted panel : 340 W, • Mounting clamps included : 4 x end clamp 35 mm 	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • "Cold Start" function • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Excellent microprocessor control guarantees high reliability • UPS auto diagnostic system • Battery charge and maintenance control • USB/RS-232 communication port
Application	...	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type	...	Rack/Tower 2-in-1 Design
Operation temp. / Relative humidity	...	0 °C ... 40 °C / 0 ~ 90 % (non-condensing)
Weight	5 kg	38.4 kg
Dimensions	...	2 pcs : 440 x 85 x 468 mm RACK 19", 2U
Manufacturer / Brand	...	EAST
Guarantee	2 years	2 years