



	ACCESS POINT RBCAP2ND cAP 2.4 GHz 300 Mbps MIKROTIK	ACCESS POINT 4G LTE +ROUTER ARCHER-MR200 2.4 GHz, 5 GHz 433 Mbps + 300 Mbps TP-LINK
		
	55.93 EUR 55.93 EUR	84.79 EUR 84.79 EUR
Frequency range	2.4 GHz	2.4 GHz , 5 GHz
Antenna type	2 x Internal antenna	3 x WiFi - built-in , 2 x 4G LTE
Standards	<ul style="list-style-type: none"> • IEEE 802.11b, • IEEE 802.11g, • IEEE 802.11n 	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3/3u
Baud rates	300 Mbps	<ul style="list-style-type: none"> • 5 GHz : 433 Mbps (max) + 2.4 GHz : 300 Mbps (max) • LTE : 150 Mbps
Transmitter power	22 dBm (max)	...
Operating system	MikroTik RouterOS	...
Modulation type	...	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM
Power supply PoE	PoE (802.3af/at) / Passive PoE	...
LAN ports	1 x 10/100 Mbps	<ul style="list-style-type: none"> • 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN
Power consumption	4 W	...
Receiver sensitivity	<ul style="list-style-type: none"> • 1M : -96 dBm • 11M : -89 dBm • 6M : -93 dBm • 54M : -74 dBm • MCS0 : -93 • MCS7 : -71 	5 GHz : <ul style="list-style-type: none"> • 11a 54M: -74dBm • 11ac HT20: -67dBm • 11ac HT40: -64dBm • 11ac HT80: -60dBm • 11n HT20: -71dBm • 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M: -76dBm • 11n HT20: -73dBm • 11n HT40: -67dBm
LTE	...	✓
QSS	...	✓
WDS	...	✓

Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • Passive PoE : 11 ... 57 V DC • 24 V / 0.2 mA (power adapter included) - via external PoE stabilizer (included) 	12 V DC / 1 A (power adapter included)
Operation temp	-40 °C ... 70 °C	0 °C ... 40 °C
Permissible relative humidity	5 % ... 95 %	95 % (non-condensing)
Main features	<ul style="list-style-type: none"> • Possibility to mount on the wall or ceiling • Mode button 	<ul style="list-style-type: none"> • SIM socket • WPS/RESET button
Weight	0.24 kg	0.26 kg
Dimensions	Ø 165 x 28 mm	202 x 163 x 34 mm
Manufacturer / Brand	MikroTik	TP-LINK
Guarantee	2 years	3 years