



	IP VANDALPROOF CAMERA TC-C35KS SPEC:13/E/Y/M/S/H/2.8MM/V4.0 - 5 Mpx 2.8 mm TIANDY	SURFACE HOUSING DS-KD-ACW3 Hikvision
		
	237.71 EUR 237.71 EUR	174.10 EUR 174.10 EUR
Number of mounted modules	...	3 pcs
Standard	IP	...
Material	...	Aluminum
Application	...	DS-KD-xx
External dimensions	...	321 x 107 x 37 mm
SAP Code	...	305700452
Resolution	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Sensor	1/2.7 " Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	104 °	...
Range of IR illumination	30 m	...
Memory card slot	Micro SD card support up to 512GB	...
Image compression method	S+265 / H.265 / H.264	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio input • Audio output • Bi-directional audio streaming support • Audio transmission via network • Compliance with the AAC standard 	...
Main stream frame rate	25 fps @ 5 Mpx 50 fps @ 2 Mpx	...
Network interface	10/100 Base-TX (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	2	...
ONVIF	✓	...

Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	...
Default IP address	DHCP or 192.168.1.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
Mobile client access ports	3000, 3001	...
PC client access ports	3000, 3001	...
Port ONVIF	80	...
Intelligent image analysis	<ul style="list-style-type: none"> • classification of people and vehicles • crossing the line (tripwire) • intrusion • video tampering • Audio detection • face detection 	...



Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Corridor mode • Day/night mode • Privacy zones • Motion Detection 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 625 mA 	...
Power consumption	≤ 7.5 W	...
Housing	Dome - Metal	...
Color	White	Graphite
"Index of Protection"	IP66	...
Mechanical protection class	IK10	...
Operation temp	-40 °C ... 65 °C	...
Weight	0.49 kg	0.47 kg
Dimensions	Ø 120 x 90 mm	...
Supported languages	Polish, English, Albanian, Arabic, Hebrew, Spanish, Dutch, Korean, French, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	...
Manufacturer / Brand	TIANDY	Hikvision
Guarantee	3 years	3 years