

	RFID PROXIMITY CARD ATLO-114*P10	IP CAMERA APTI-AI203PV21-28W - 1080p 2.8 mm
		
	5.07 EUR 5.07 EUR	30.28 EUR 30.28 EUR
Standard	...	TCP/IP
Sensor	...	1/2.9 " Progressive Scan CMOS
Matrix size	...	2.1 Mpx
In package	10 pcs The price for package	...
Standard	Unique EM 125kHz	...
Compatibility	EM4100/4102	...
Possibility of programming the serial number (ID)	—	...
Ability to write to internal memory	—	...
Serial Number overprint	—	...
Resolution	...	1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 mm
View angle	...	105 °
Range of IR illumination	...	30 m
Main features	<ul style="list-style-type: none"> • Range : ~ 15 cm • The TK-4100 chip 	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	—
Main stream frame rate	...	25 fps @ 1080p
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in - port 80
Max. number of on-line users	...	10
ONVIF	...	✓

Main features	...	<ul style="list-style-type: none"> • Intelligent image analysis : intrusion, motion detection based on human detection • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • Possibility to change the resolution, quality and bit rate • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Motion Detection • Privacy zones • Day/night mode • Auto White Balance • Mirror - Mirror image • RESET button - on the cable • Sharpness - sharper image outlines
Mobile phones support	...	<p>Port no.: 80 or access by a cloud (P2P)</p> <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address	...	192.168.1.168
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	80
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 220 mA
Power consumption	...	≤ 2.7 W

Housing	...	Dome, Metal + Plastic
Vandal-proof	...	—
Color	...	White
"Index of Protection"	...	IP65
Operation temp	...	-20 °C ... 60 °C
Weight	0.006 kg	0.23 kg
Dimensions	85 x 54 x 2 mm	Ø 108 x 83 mm
Supported languages	...	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, Portuguese, Russian, Turkish
Manufacturer / Brand	ATLO	APTI
Guarantee	2 years	2 years