




	<a href="#">SWITCH POE GTX-CLM1-10-8G2G 8-PORT</a>	<a href="#">POE SWITCH / EXTENDER PFT1310 3-PORT</a>	<a href="#">UPS AT-UPS2000R/2-RACK 2000 VA EAST</a>
			
	1640.24 SEK 1640.24 SEK	218.26 SEK 218.26 SEK	2785.87 SEK 2785.87 SEK
Power adapter type	...	...	Line-interactive
Nominal power	...	...	1200 W
Apparent Power	...	...	2000 VA
Input voltage	...	...	230 V AC $\pm$ 25 %
Input frequency	...	...	50 / 60 Hz (auto detection)
LAN ports	<ul style="list-style-type: none"> <li>• 8 x RJ45 ( 2 x Hi-PoE + 6 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 - Uplink</li> </ul>	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at),</li> <li>• 2 x RJ45 10/100 Base-T + PoE (802.3af)</li> </ul>	...
Output voltage	...	...	230 V AC $\pm$ 10 % (Approximated Sine Wave)
Management	✓	—	...
Output frequency	...	...	50 / 60 Hz $\pm$ 1 %
Voltage adjustment	...	...	—
Transmission speed	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE	10 / 100 Mbps	...
Frequency adjustment	...	...	—
Transfer time	...	...	2 ... 7 ms (typical), max. 10 ms
Charging time (recover to 90% capacity)	...	...	$\leq$ 8 hours
Operation modes	<ul style="list-style-type: none"> <li>• N - Normal - the device operates as normal PoE switch</li> <li>• V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports</li> <li>• S - Extend - Range : 250 m @ 10 Mbps</li> </ul>	...	...
Default IP address	192.168.2.1	...	...
Default admin user / password	admin / admin	...	...
Battery	...	...	2 pcs - 12V/9Ah AGM
Power consumption	...	0.3 W	...
Maximal output power	<ul style="list-style-type: none"> <li>• 90 W / port Hi-PoE - 1, 2 ports</li> <li>• 30 W / port PoE - 3 ... 8 ports</li> </ul>	<ul style="list-style-type: none"> <li>• 15.4 W @ port PoE - First device</li> <li>• 3 W @ port PoE - Second device in cascade</li> </ul>	...

Range	...	100 m - Input 100 m - Output	...
Maximal total power	120 W	...	...
LED diodes	PWR, PoE, Link/Act	LAN, PoE	...
Estimated battery operation time	...	...	<ul style="list-style-type: none"> <li>• 62 minutes @ 100 W,</li> <li>• 31 minutes @ 200 W,</li> <li>• 16 minutes @ 300 W,</li> <li>• 9.5 minutes @ 500 W,</li> <li>• 2.5 minutes @ 800 W,</li> <li>• 1 minute @ 1000 W</li> </ul>
Certificates	CE, FCC, RoHS	...	...
Power supply	48 ... 57 V DC, Power adapter included	PoE (802.3af/at)	...
Number of outputs	...	...	3 pcs - 2 x CEE 7/3 (Schuko), 1 x IEC C13
Housing	Metal	Plastic, DIN, TS-35 rail mounting	...
Management software	...	...	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)
Operation temp	-10 °C ... 55 °C	...	...
Protections	Overvoltage $\pm$ 4 kV	Overvoltage	<ul style="list-style-type: none"> <li>• Fuse</li> <li>• Short-circuit</li> <li>• Overload</li> <li>• Overvoltage - RJ45</li> <li>• Ethernet filter</li> <li>• Output voltage filtering</li> <li>• DC filter to eliminate interferences - EMI/RFI</li> </ul>
Operation state indication	...	...	<ul style="list-style-type: none"> <li>• LCD display: in/out voltage level, in frequency, battery capacity, load, alarm,</li> <li>• Sound signaling</li> </ul>

Main features	<ul style="list-style-type: none"> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Auto-learning and Auto-aging functions support for MAC addresses</li> <li>• QoS - mechanisms, which provide the high quality of transmission</li> <li>• MTBF (Mean Time Between Faults) : 50000 h</li> </ul>	<ul style="list-style-type: none"> <li>• Possibility to connecting in cascade</li> <li>• The device can function as a LAN network and PoE power extender</li> </ul>	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• "Cold Start" function</li> <li>• The device works with power supply adapters having Active Power Factor Correction (APFC)</li> <li>• Remote management - UPSmart application included</li> <li>• Built-in EMI, RFI filter</li> <li>• Excellent microprocessor control guarantees high reliability</li> <li>• self test feature</li> <li>• 2 x RJ-45 - Input / Output</li> <li>• Port USB 2.0 - Access from PC</li> </ul>
Application	...	...	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>
Housing type	...	...	Rack 19"
Operation temp. / Relative humidity	...	-30 ... 65 °C / 10 ... 90 %	0 °C ... 40 °C / 20 ... 90 %
Weight	0.45 kg	0.05 kg	15.0 kg
Dimensions	185 x 95 x 27 mm	79 x 52 x 23 mm	<ul style="list-style-type: none"> <li>• 440 x 308 x 132 mm, RACK 19", 3U</li> <li>• 485 x 345 x 132 mm (with bracket)</li> </ul>
Manufacturer / Brand	...	...	EAST
Guarantee	2 years	2 years	2 years