





	SMART VALVE FOR THE IRRIGATION SYSTEM ATLO-VR1C-BLE-TUYA Bluetooth BLE, Tuya Smart	SMART DUAL VALVE FOR THE IRRIGATION SYSTEM ATLO-VR2G-BLE-TUYA Bluetooth BLE, Tuya Smart	SMART GARAGE DOOR CONTROLLER ATLO-GDC2-TUYA Wi-Fi, Tuya Smart	DUAL SMART LIGHT SWITCH ATLO-WB2-TUYA Wi-Fi, Tuya Smart
				
	20.69 GBP 20.69 GBP	43.90 GBP 43.90 GBP	12.51 GBP 12.51 GBP	8.88 GBP 8.88 GBP
Application	irrigation control	irrigation control - 2 Zones	garage doors	Works with lighting - switching on/off
Type (size)	3/4 "	3/4 "
Number of inputs	1 x Reed switch	...
Rated voltage	100 ... 240 V AC, 50 / 60 Hz
Working pressure	0.02 ... 0.8 MPa / 2.9 ... 116 psi	0.05 ... 0.8 MPa / 7.25 ... 116 psi
Water flow	13 ... 33 l/min
Maximum power	300 W (for each output)
Break distance	3 ... 15 mm	...
Rated current	max. 10 A
Number of buttons	2
Opening/closing time	5 ... 10 s	5 ... 10 s
Number of outputs	1 x NO	2
Connector type	screw terminals
Wireless	Bluetooth	<ul style="list-style-type: none"> • Bluetooth, • 2.4 GHz Wi-Fi IEEE 802.11 b/g/n - Bluetooth/Wi-Fi gateway 	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Radio communication range (at open area)	15 m	<ul style="list-style-type: none"> • 15 m - Bluetooth • The range limited only by the availability of the Wi-Fi network - Bluetooth/Wi-Fi gateway
Mobile phones support	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Permissible relative humidity	≤ 80 %

Main features	<ul style="list-style-type: none"> • schedule - 20 tasks, • timer, • manual watering (app or button), • delay after rain : 24, 48, 72 h - the device will not turn on the sprinklers if it is raining, • remote access - Bluetooth/Wi-Fi gateway, • voice control • STATUS indicator • Low current consumption • Easy installation - the valve is mounted directly on the tap • 3/4" / 1/2" Adapter (included) 	<ul style="list-style-type: none"> • schedule, • timer, • manual watering (app or button), • delay after rain : 1 ... 7 days - the device will not turn on the sprinklers if it is raining, • remote access - Bluetooth/Wi-Fi gateway (included), • voice control • 2 x STATUS indicator • Low current consumption • Easy installation - the valve is mounted directly on the tap • 2 x 3/4" / 1/2" Adapter (included) 	<ul style="list-style-type: none"> • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • Magnetic contact included • Garage door open alarm • Opening and closing history • STATUS indicator • ON/OFF button • For indoor use 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication
Housing	Plastic (ABS) + Nylon, UV-resistant, Waterproof	Plastic (ABS) + Nylon, UV-resistant, Waterproof	...	Plastic
"Index of Protection"	IP55	IP55
Color	Black + Green	Gray + Black	...	White
Power supply	2 x 1.5V, type AA/LR6/FR6 battery (not included)	4 x 1.5V, type AA/LR6/FR6 battery (not included)	100 ... 240 V AC, 50 / 60 Hz	...
Operation temp	4.5 °C ... 45 °C	4.5 °C ... 45 °C	0 °C ... 40 °C	-20 °C ... 50 °C
Weight	0.19 kg	0.4 kg	0.16 kg	0.098 kg
Dimensions	137 x 68 x 89 mm	141 x 122 x 58 mm	<ul style="list-style-type: none"> • 90 x 39 x 25 mm • 5 m (cable length) - Reed switch • 1 m (cable length) - Power supply 	87 x 86 x 41 mm
Guarantee	2 years	2 years	2 years	2 years