



	<a href="#">EXPANSION PLUG KS-10/6X120 KLIMAS</a>	<a href="#">SWITCH POE RG- CS83-12GT4XS-P 12-PORT RUIJIE</a>
		
	0.25 GBP 0.25 GBP	564.06 GBP 564.06 GBP
Material	<ul style="list-style-type: none"> <li>Expansion plug, Polypropylene</li> <li>Screw, Steel galvanized</li> </ul>	...
Drilling diameter	10 mm	...
Expansion plug length	60 mm	...
Screw dimensions	Ø 6 x 120 mm, SW-10	...
Application	<ul style="list-style-type: none"> <li>Concrete</li> <li>Solid clay brick</li> <li>Solid sand-lime brick</li> </ul>	...
LAN ports	...	<ul style="list-style-type: none"> <li>12 x RJ45 10/100/1000 Base-T ( 12 x PoE (802.3af/at) ),</li> <li>4 x port SFP - Uplink</li> <li>1 x RJ45 - Configuration possibility from PC,</li> <li>1 x USB - Configuration possibility from PC</li> </ul>
Management	...	✓
Number of fan coolers	...	1
Transmission speed	...	<ul style="list-style-type: none"> <li>10/100/1000 Mbps : 12 LAN &amp; PoE ports Uplink ports</li> <li>1/10 Gbps - 4 x SFP ports</li> </ul>
Maximal total power	...	370 W
Switching capacity	...	104 Gb/s
Forwarding rate	...	78 Mpps
MAC addresses table	...	16k
Mobile phones support	...	Android: Free application <a href="#">Ruijie Reyee</a> iOS (iPhone): Free application <a href="#">Ruijie Reyee</a>

Main features	...	<ul style="list-style-type: none"> <li>• Can be mounted in a Rack cabinet</li> <li>• Switch is managed through the web and the cloud (Ruijie Rejee application)</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs</li> <li>• DHCP client, DHCP server, DHCP Relay support</li> <li>• Loop back detection</li> <li>• Spanning Tree STP/RSTP/MSTP</li> <li>• IGMP Snooping V1/V2/V3</li> <li>• DHCP snooping support</li> <li>• Loop Protection</li> <li>• MTBF (Mean Time Between Faults) &gt; 24.14 years</li> </ul>
Certificates	...	CE, RoHS
Protections	...	Protection against lightning discharges : 10 kV
Housing	...	Desktop, Metal
Power supply	...	100 V ... 240 AC
Power consumption	...	≤ 405 W
Operation temp	...	0 °C ... 45 °C
Weight	...	2.9 kg
Dimensions	...	442 x 222 x 44 mm
Manufacturer / Brand	KLIMAS	RUIJIE
Guarantee	2 years	3 years