

	DOORBELL BUTTON PD-1 ORNO	IP CAMERA BCS-L-DMIP22FSR3-AI1 - 1080p 2.8 mm BCS Line
		
	3.93 CHF 3.93 CHF	217.26 CHF 217.26 CHF
Standard	...	TCP/IP
Sensor	...	1/2.8 " Progressive Scan CMOS
Matrix size	...	2.1 Mpx
Main features	Housing - Plastic, Surface-mounted	...
Resolution	...	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	...	2.8 mm
View angle	...	• 107 ° (manufacturer data) • 97 ° (our tests result)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG / AI Coding
Range of IR illumination	...	30 m
Alarm inputs / outputs	...	1 / 1
Main stream frame rate	...	25 fps - 1080p
Network interface	...	10/100 Base-T (RJ-45)
Audio	...	• Microphone built-in, • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection • Compliance with the AAC standard
WEB Server	...	Built-in
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Max. number of on-line users	...	20
ONVIF	...	21.12
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80

RTSP URL	...	• Main stream : rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 • Sub stream : rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1
Main features	...	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Image rotation and mirror • Motion Detection - max. 4 configurable zones • Privacy zones - max. 4 • SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area - classification of people and vehicles
Power supply	max. 250 V / 1 A	• PoE (802.3af), • 12 V DC / 600 mA
Power consumption	...	≤ 7.2 W
Housing	...	Dome, Metal
Color	...	White
"Index of Protection"	IP44	IP67
Vandal-proof	...	IK10
Operation temp	...	-40 °C ... 60 °C
Supported languages	...	Polish, English, French, Spanish, Dutch, German, Portuguese, Romanian, Turkish, Italian
Weight	0.035 kg	0.43 kg
Dimensions	81 x 33 x 20 mm	Ø 111 x 65 mm
Manufacturer / Brand	ORNO	BCS Line
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00