





	TV OR MONITOR MOUNT BS-106S	ACCESS POINT 4G LTE +ROUTER TL-MR6400 300Mb/s TP-LINK	PROJECTOR MOUNT MC-515S	ANGULAR PLUG LE-50461 230 V 16 A LEGRAND
				
	7.00 GBP 7.00 GBP	65.17 GBP 65.17 GBP	14.22 GBP 14.22 GBP	9.18 GBP 9.18 GBP
Frequency range	...	2.4 GHz
Rated voltage	230 V / 50 Hz
Mounting standard	VESA : 75, 100, 200, 400 x 200
Maximal current load	16 A
Maximal total load	3500 W
Screen size range	23 " ... 42 "
Projector mounting holes distances	Ø 130 ... 320 mm	...
Grounding	✓
Bearing capacity	45 kg	...	10 kg	...
Distance from mounting surface	19 mm from wall	...	100 mm or 170 mm from ceiling	...
Electrical cable	max. 3 x 1.5 mm ²
Cable terminals	screw terminals
Tilt adjustment	—	...	-15 ° ... 15 °	...
Plug type	CEE 7/7
Horizontal rotation	—	...	360 °	...
Antenna type	...	2 x WiFi built-in , 2 x 4G LTE - 2 x SMA socket - Possibility to connect the wire antenna
Socket type	CEE 7/5
Rotation in the plane of the screen	—
Standards	...	802.11n/g/b IEEE 802.3/3u
Color	Black	...	Silver	White / Gray
Baud rates	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 Mbps
Modulation type	...	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM
LAN ports	...	• 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN
Receiver sensitivity	...	• 11g 54M: -74dBm • 11n HT20: -71dBm • 11n HT40: -67dBm
LTE	...	✓
QSS	...	✓
WDS	...	✓

Power supply	...	9 V DC / 1 A (power adapter included)
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	max. 95 % (non-condensing)
Main features	...	<ul style="list-style-type: none"> • SIM socket • WPS/RESET button 	...	Plug equipped with an additional socket outlet, compliant with the Uni-Schuko standard
Weight	1.45 kg	0.354 kg	0.96 kg	0.07 kg
Dimensions	455 x 260 x 19 mm	202 x 141 x 34 mm	max. Ø 320 x 170 mm	79 x 75 x 55 mm
Manufacturer / Brand	...	TP-LINK	...	LEGRAND
Guarantee	2 years	3 years	2 years	2 years