



	WIRELESS DOOR CHIME ATLO-DBB-TUYA	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE56D0T- IT3F(2.8mm)(C) - 1080p Hikvision
		
	6.35 USD 6.35 USD	67.47 USD 67.47 USD
Signaling mode	Optical - sound signaling	...
Number of ring-tones	52	...
Standard	...	AHD / HD-CVI / HD-TVI / CVBS
Sensor	...	Progressive Scan CMOS
Volume adjustment	4 volume levels, 10 ... 90 dB	...
Matrix size	...	2.1 Mpx
Operation range	80 m in open area	...
Resolution	...	1920 x 1080 - 1080p
Frequency band	433.92 MHz \pm 0.2	...
Range of IR illumination	...	40 m
IR illuminator power adjustment	...	Automatic
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 106 ° (manufacturer data) • 101 ° (our tests result)
Main features	<ul style="list-style-type: none"> • Low power consumption • Receiver sensitivity : -110 dBm • Simple and quick device installation 	...
IR illuminator support	...	ICR - Movable InfraRed filter
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 V _{pp} / 75 Ω

Main features	...	<ul style="list-style-type: none"> • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • D-WDR - Wide Dynamic Range • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Sharpness - sharper image outlines
OSD menu	...	—
"Index of Protection"	...	IP67
Power supply	100 ... 240 V AC	12 V DC / 250 mA
Power consumption	≤ 0.5 W	≤ 3 W
Housing	Plastic	Dome, Plastic
Vandal-proof	...	—
Color	Black	White
Operation temp	...	-40 °C ... 60 °C
Weight	0.06 kg	0.21 kg
Dimensions	82 x 82 x 65 mm	Ø 110 x 93 mm
Manufacturer / Brand	...	Hikvision
SAP Code	...	300613493
Guarantee	2 years	3 years