




	TV OR MONITOR MOUNT BRATECK-LPA63-446	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR APTI- XB0401H-S34 4 CHANNELS
		
	20.64 EUR 20.64 EUR	69.19 EUR 69.19 EUR
Standard	...	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Video inputs	...	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Mounting standard	VESA : 75, 100, 150x100, 150, 200x100, 200, 300x200, 300, 400x200, 400x300, 400	...
Screen size range	32 " ... 70 "	...
Bearing capacity	40 kg	...
Video outputs	...	<ul style="list-style-type: none"> • 1 pcs HDMI : 1920 x 1080 (max) • 1 pcs VGA • 1 pcs Composite Video (CVBS) - BNC socket
Distance from mounting surface	62 ... 468 mm	...
Audio inputs	...	<ul style="list-style-type: none"> • 4 - Audio support via coaxial cable, • 2 pcs CINCH
Audio outputs	...	1 pcs CINCH
Tilt adjustment	-15 ° ... 5 °	...
Horizontal rotation	-60 ° ... 60 °	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Rotation in the plane of the screen	± 3 °	...

Image records resolutions	...	<ul style="list-style-type: none"> • AHD / HD-TVI : 8M-N - 1920 x 2160 px, 5 Mpx - 2592 x 1944 px, 5M-N - 1296 x 1944 px, 4 Mpx - 2560 x 1440 px, 4M-N - 1280 x 1440 px, 3 Mpx - 2048 x 1536 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • HD-CVI : 8M-N - 1920 x 2160 px, 4 Mpx - 2560 x 1440 px, 4M-N - 1280 x 1440 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • CVBS : 960H - 960 x 576 px, • IP : max. 5 Mpx - 2592 x 1944 px
Recording speed adjustment	...	<ul style="list-style-type: none"> 5 Mpx IP @ 1 ... 25 fps 8M-N @ 1 ... 8 fps 5 Mpx @ 1 ... 6 fps 5M-N @ 1 ... 10 fps 4 Mpx @ 1 ... 8 fps 4M-N @ 1 ... 15 fps 3 Mpx @ 1 ... 9 fps 3M-N @ 1 ... 18 1080p @ 1 ... 15 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps <p>for each channel</p>
Operation modes	...	<ul style="list-style-type: none"> • 4 x AHD / HD-CVI / HD-TVI / CVBS + 2 x IP max. 5 Mpx • 2 x AHD / HD-CVI / HD-TVI / CVBS + 7 x IP max. 5 Mpx • 16 x IP max. 5 Mpx <p>All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras</p>
Recording modes	...	Motion Detection, Schedule
Supported hard drives	...	1 x 8 TB SATA
External storage devices backup	...	Records backup at (.avi) format to USB (pendrive)

Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time
Network functions	...	<ul style="list-style-type: none"> • Network Client Software (iVMS320): live view, playback and backup of the records • IE browser: live view, playback and backup of the records and configuration of the recorder parameters
Mobile phones support	...	Port no.: 6000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision, Android: Free application iVMS320 • iOS (iPhone): Free application BitVision, iOS: Free application iVMS320
Default IP address	...	192.168.1.88
Default admin user / password	...	admin / 12345
Web browser access ports	...	80, 5000, 554
PC client access ports	...	80, 5000, 554
Mobile client access ports	...	80, 5000, 6000
Alarm inputs / outputs	...	4 / 1
PTZ control	...	Pelco-D, Pelco-P
Motion Detection	...	Split the screen into zones : 22 x 18 motion zones
USB	...	2 pcs USB 2.0
Mouse support	...	✓
IR remote controller in the set	...	—
Power supply	...	12 V DC / 2 A (power adapter included)
Color	Black	Black
Weight	4.44 kg	0.71 kg
Dimensions	455 x 420 x (62 ... 468) mm	260 x 226 x 45 mm
Supported languages	...	Polish, English, Bulgarian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian

Country of origin	...	China
Manufacturer / Brand	BRATECK	APTI
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00