

	<a href="#">AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR XVR5232AN-I3 32 CHANNELS DAHUA</a>	<a href="#">SWITCHING ADAPTER PS65-15-DIN ACO</a>	<a href="#">INDOOR PANEL DS-KH7300EY-WTE2 Hikvision</a>
			
	889.53 EUR 889.53 EUR	59.10 EUR 59.10 EUR	503.28 EUR 503.28 EUR
Compatibility	...	...	Hikvision 2-wire modular video doorphones
Application	...	ACO Video Doorphones	...
Adapter type	...	Switching	...
Shield	...	...	7 " - capacitive touch screen
Resolution	...	...	1024 x 600
Power voltage	...	100 ... 240 V AC	...
Internal memory	...	...	128 MB (built-in)
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...	...
Output voltage	...	15 V DC	...
Video inputs	32 pcs BNC	...	...
Output voltage adjustment	...	—	...
Maximal load	...	4 A	...
Output power	...	65 W	...
Video outputs	• 1 pcs HDMI 4K (1080p with AI functions turned on) • 1 pcs VGA	...	...
Number of outputs	...	2 pcs	...
Efficiency	...	≤ 91 %	...
Housing type	...	DIN	...
Protections	...	• Short-circuit • Overload • Overheat	...
Audio inputs	1 pcs CINCH , 32 Channels - Audio support via coaxial cable, HD-CVI only	...	...
Audio outputs	1 pcs CINCH	...	...
Image compression method	AI Coding / H.265+ / H.265 / H.264+ / H.264	...	...
Controlling	...	...	Touch control keys + capacitive touch screen
Default administrator password	...	...	— The administrator password should be set at the first start

Default password for securing the zone	...	...	—
Alarm inputs	...	...	1
Alarm outputs	...	...	—
Power consumption	...	...	≤ 5 W
Operation temp	...	...	-10 °C ... 50 °C
Image records resolutions	<ul style="list-style-type: none"> <li>• AHD / HD-CVI / HD-TVI : 5M-N - 1296 x 1944 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720</li> <li>• CVBS : 960H - 960 x 576</li> <li>• IP : max. 6 Mpx - 3072 x 2048</li> </ul>	...	...
SAP Code	...	...	305304184
Recording speed adjustment	6 Mpx IP @ 1 ... 25 fps 5M-N @ 1 ... 10 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 for each channel	...	...
Operation modes	32 x AHD / HD-CVI / HD-TVI / CVBS / IP	...	...
Recording modes	Manual, Motion Detection, Schedule	...	...
Supported hard drives	2 x 16 TB SATA	...	...
External storage devices backup	Save single frames and whole records from DVR drive to the USB drive	...	...
Searching and playback the records	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) 1/4/9/16 channel synchronous playback	...	...
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users	...	...

Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>  See how to configure the P2P function in Dahua recorders and how to enable the mobile application	...	...
Alarm inputs / outputs	—	...	...
PTZ control	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P	...	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...	...

Main features	<ul style="list-style-type: none"> <li>• Cooperation with Dahua devices working in the concept of the Internet of Things (IoT),</li> <li>• POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window,</li> <li>• Coax Audio/Alarm support,</li> <li>• Intelligent image analysis : crossing the line (tripwire), crossing the line (tripwire), classification of people and vehicles,</li> <li>• advanced face and vehicle recognition and search functions</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles (tripwire, intrusion)</li> <li>• Support for up to 10 face databases, including 10 000 face images</li> <li>• Detection of faces not included in the device database</li> <li>• Searching for faces in recordings based on max 8 selected photos with the ability to independently set the similarity threshold for each photo</li> <li>• SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle</li> </ul>	...	<ul style="list-style-type: none"> <li>• Wi-Fi Module - IEEE 802.11 b/g/n,</li> <li>• Microphone built-in,</li> <li>• Speakers built-in,</li> <li>• Bidirectional communication,</li> <li>• Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume,</li> <li>• Automatically capture and save photos if there is no response to the bell button,</li> <li>• The ability of direct communication between two or more panels,</li> <li>• The panel is addressed using rotary switches</li> <li>• Register a short voice message if there is no response to the bell button</li> <li>• Support for capturing a photo during video calls</li> <li>• Micro SD memory cards up to 128GB support (possible local recording)</li> <li>• In addition, the device has the ability to work with the <b>Hik-Connect</b> application on mobile devices</li> </ul>
Mouse support	✓	...	...
IR remote controller in the set	—	...	...
USB	1 pcs USB 3.0 1 pcs USB 2.0	...	...
Power supply	12 V DC / 5 A (power adapter included)	...	48 V DC - HIKVISION 2-wire
Color	Black	...	Black + Silver
Weight	1.96 kg	0.22 kg	0.35 kg
Dimensions	375 x 289 x 53 mm	70 x 91 x 59 mm	190 x 138 x 20 mm

Supported languages	Polish, English, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian	...	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand	DAHUA	ACO	Hikvision
Guarantee	3 years	3 years	3 years