




	STRAIGHT SOCKET LE-50112 230 V 16 A LEGRAND	ACCESS CONTROLLER MC16-PAC-ST-2-KIT ROGER	INDOOR PANEL VTH5421HW-W Wi-Fi / IP DAHUA
			
	25.03 EUR 25.03 EUR	524.92 EUR 524.92 EUR	306.82 EUR 306.82 EUR
Compatibility	DAHUA
Rated voltage	230 V / 50 Hz
Number of served transitions	...	2 (two-way)	...
Shield	7 " capacitive touch screen
Maximal current load	16 A
Number of supported readers	...	8	...
Resolution	1024 x 600
Grounding	✓
Internal memory	—
Electrical cable	max. 3 x 2.5 mm ²
Number of users	...	unlimited (purchase of the appropriate license required)	...
Memory card slot	Micro SD memory cards up to 64GB support (possible local recording)
Cable terminals	automatic spring terminals
Wi-Fi interface	2.4 GHz IEEE 802.11 b/g/n
Socket type	CEE 7/5
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.	...
Buffer memory	...	8 000 000 events buffer	...
"Index of Protection"	IP44
Number of access zones	...	4	...
IK rating	IK08
Number of alarm zones	...	4	...
Battery backup support	...	12 V / 20 Ah	...
Communication	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface 	...

Main features	<ul style="list-style-type: none"> • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • The ability to automatically take and save photos if you do not answer to the bell button, • The ability to record a short video message in the absence of a response to the bell button, • IP Dahua cameras support
Controlling	capacitive touch screen
Alarm inputs	6 (1 - as a bell)
Alarm outputs	1
Main features	...	<ul style="list-style-type: none"> • Metal housing • The MCX2D I/O expander included • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	...
Power supply	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 1 A
Power consumption	<ul style="list-style-type: none"> ≤ 6 W (operation) ≤ 2 W (standby)
Operation temp	...	5 °C ... 40 °C	-10 °C ... 55 °C
Color	Black	...	White
Permissible relative humidity	...	10 % ... 95 % (non-condensing)	...
Weight	0.084 kg	4.25 kg	0.36 kg
Dimensions	Ø 56 x 115 mm	405 x 365 x 123 mm	189 x 130 x 27 mm
Supported languages	Polish, English
Manufacturer / Brand	LEGRAND	ROGER	DAHUA

Guarantee	2 years	3 years	3 years
-----------	---------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00