



	RFID PROXIMITY CARD ATLO-104N*P200	AHD, HD-CVI, HD-TVI CAMERA APTI-H51V21-28W 2Mpx / 5Mpx 2.8 mm
		
	59.79 EUR 59.79 EUR	29.85 EUR 29.85 EUR
Standard	...	AHD, HD-CVI, HD-TVI
In package	200 pcs The price for package	...
Standard	Unique EM 125kHz	...
Sensor	...	1/3 " Progressive Scan CMOS
Compatibility	EM4100/4102	...
Matrix size	...	5 Mpx
Possibility of programming the serial number (ID)	—	...
Ability to write to internal memory	—	...
Serial Number overprint	✓	...
Main features	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + WEG24A • Range : ~ 11 cm • The TK-4100 chip 	...
Resolution	...	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps
Range of IR illumination	...	20 m
IR illuminator power adjustment	...	Automatic
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 89 ° (manufacturer data) • 82 ° (our tests result)
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch
OSD menu	...	✓

Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines • Coaxial audio - HD-TVI only
Housing	...	Dome - Metal
Color	...	White
Vandal-proof	...	—
"Index of Protection"	...	IP67
Power supply	...	12 V DC / 250 mA
Power consumption	...	≤ 3 W
Operation temp	...	-20 °C ... 60 °C
Weight	0.006 kg	0.42 kg
Dimensions	86 x 54 x 1 mm	Ø 97 x 91 mm
Supported languages	...	Polish, English
Manufacturer / Brand	ATLO	APTI
Guarantee	2 years	2 years