






	MOUNTING PROFILE USP- SM-1650 FOR SOLAR PANELS	REAR SUPPORT FOR THE MOUNTING PROFILE USP- TN-600 FOR SOLAR PANELS	ZIGBEE REPEATER ATLO- RP1-TUYA Wi-Fi, Tuya Smart	EXPANSION PLUG JK-12X220/M5 EBOLT	COAXIAL CABLE RG-174 50 Ω
					
	27.04 EUR 27.04 EUR	6.44 EUR 6.44 EUR	13.31 EUR 13.31 EUR	1.95 EUR 1.95 EUR	0.36 EUR 0.36 EUR
Material	Aluminum	Aluminum
Network interface	ZigBee - 2.4 GHz
In section	100 m . Price for 1m when buying a whole roll
Operating frequency	2400 ... 2483 MHz
Transmitter power	10 dBm
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized • mounting screw, Steel galvanized 	...
Drilling diameter	12 mm	...
Power supply	5 V DC - Port USB
Current consumption	max. 1000 mA
Inner conductor	7 x Ø 0.16 mm Cu Stranded wire
Expansion plug length	215 mm	...
Color	White
Dielectric	Ø 1.6 mm PE full
Shield	—
Screw dimensions	Ø 8 x 220 mm, Internal thread M5	...
Operation temp	-10 °C ... 50 °C
Permissible relative humidity	≤ 95 % (non-condensing)
Screw	Ø 5 x 16 mm	...
Application	for Styrofoam 150 mm	...
Weight	0.21 kg	0.32 kg	0.005 kg
Braid	64 x Ø 0.1 mm Stranded wire Cu
Impedance	50 Ω
Outer coating	Ø 2.8 mm PVC
Dimensions	1650 x 50 x 50 mm	600 x 35 x 35 mm	39 x 22 x 8 mm
Manufacturer / Brand	ATLO	EBOLT	...
Cable attenuation at 100m section	17.6 dB @ 30 MHz 21.1 dB @ 50 MHz 28.2 dB @ 100 MHz 21.6 dB @ 146 MHz 80 dB @ 440 MHz 96 dB @ 1000 MHz 240 dB @ 2400 MHz
Guarantee	2 years	2 years	2 years	2 years	2 years