



| | LOW RESISTANCE METER UT-620A UNI-T | CABLE PAIR DETECTOR WITH RJ-45 CABLE TESTER UT-682 UNI-T |
|--------------------------------------|--|---|
| |  |  |
| | 575.72 EUR 575.72 EUR | 29.55 EUR 29.55 EUR |
| Tested cables | ... | UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C) |
| Operation temp | ... | 0 °C ... 40 °C |
| Permissible relative humidity | ... | 20 % ... 75 % |
| Resistance measurement | 120 mΩ ± (0.25% + 25) @ 0.01 mΩ , 600 mΩ ± (0.25% + 25) @ 0.01 mΩ , 6 Ω ± (0.25% + 25) @ 0.0001 Ω , 60 Ω ± (0.25% + 25) @ 0.001 Ω , 600 Ω ± (0.25% + 25) @ 0.01 Ω , 6 kΩ ± (0.75% + 30) @ 0.0001 kΩ | ... |
| Automatic change of measuring ranges | — | ... |
| RS-232 | — | ... |
| USB | ✓ | ... |
| Main features | <ul style="list-style-type: none"> • Hold - stopping the meter reading, • 4-lead measurement, • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction, • The set includes a practical case | <ul style="list-style-type: none"> • Test for the presence of a short circuit, open circuit • Polarity indicator for telephone wire pairs : ± (5V ... 52V) • The maximum length of the telephone line : 3000 m • Optical - sound signaling • Low battery indicator |
| Power supply | Built-in 7.4V / 4000mAh battery, 9V / 4A power adapter included | 2 x 9V, type 6F22 battery (included) |
| Weight | 1.33 kg | <ul style="list-style-type: none"> • 0.11 kg - Transmitter • 0.14 kg - Receiver |
| Dimensions | 269 x 182 x 60 mm | <ul style="list-style-type: none"> • 125 x 48 x 29 mm - Transmitter • 194 x 50 x 30 - Receiver |
| Manufacturer / Brand | UNI-T | UNI-T |
| Guarantee | 2 years | 2 years |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00