



	<a href="#">SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH-2WIRE-SET 2 PCS SET ATTE</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR TC-H344S SPEC:25X/I/E+/A/V3.0 - 3.7 Mpx 4.8 ... 120 mm TIANDY</a>
		
	1287.75 SEK 1287.75 SEK	11287.75 SEK 11287.75 SEK
Standard	...	IP
Sensor	...	1/2.7 " Progressive Scan CMOS
Connectors	<ul style="list-style-type: none"> <li>• 1 pcs RJ45</li> <li>• 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm<sup>2</sup> ( 22 ... 12 AWG )</li> </ul>	...
LAN ports	1 pcs RJ45 100 Mbps	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	4.8 ... 120 mm
View angle	...	58 ° ... 2.8 °
Optical zoom	...	x 25
Digital zoom	...	x 16
Range of IR illumination	...	150 m
Video output	...	—
Preset rotation speed	...	<ul style="list-style-type: none"> <li>• 240 °/s (horizontal)</li> <li>• 180 °/s (vertical)</li> </ul>
Rotation speed (manual control)	...	<ul style="list-style-type: none"> <li>• 0.1 °/s ... 200 °/s (horizontal),</li> <li>• 0.1 °/s ... 120 °/s (vertical)</li> </ul>
Horizontal rotation range	...	360 ° - continuous
Terminals	<p>ETH-2WIRE-TX :</p> <ul style="list-style-type: none"> <li>• PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+/-": 3, 6 pins) or ("+"-": 4, 5 pins; "+/-": 7, 8 pins)</li> <li>• Power</li> <li>• DATA - 2-wire</li> </ul> <p>ETH-2WIRE-RX :</p> <ul style="list-style-type: none"> <li>• PoE OUT - Passive PoE ("+"-": 4, 5 pins; "-": 7, 8 pins)</li> <li>• Power</li> <li>• DATA - 2-wire</li> </ul>	...

Transmission speed	100 Mbps	...
Vertical rotation range	...	-16 ° ... 90 °
RS-485 interface	...	✓
Number of presets	...	500
Horizontal scan	...	✓
Route settings	...	8
Image compression method	...	S+265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	1 / 1
Audio	...	• Audio input • Audio output
Main stream frame rate	...	25 fps @ 3.7
Transmission range	<ul style="list-style-type: none"> <li>• 300 m @ 2-wire : UTP,</li> <li>• 100 m @ 2-wire : OMY-2X0.75</li> <li>• 100 m @ UTP : Switch PoE - ETH-2WIRE-TX</li> <li>• 100 m @ UTP : ETH-2WIRE-RX - IP Camera</li> </ul>	...
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
LED indicators	<ul style="list-style-type: none"> <li>• Power</li> <li>• LAN</li> <li>• 2-wire</li> </ul>	...
Max. number of on-line users	...	7
ONVIF	...	✓
Memory card slot	...	Micro SD card support up to 512GB
Mobile phones support	...	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>
Default IP address	...	192.168.1.2
Protections	<ul style="list-style-type: none"> <li>• Overvoltage - LAN, DATA</li> <li>• Protection against reverse polarity connection - Power</li> <li>• Overload 0.6 A - PoE IN ETH-2WIRE-TX</li> </ul>	...

Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	...	3000, 3001
PC client access ports	...	3000, 3001
Port ONVIF	...	80
Main features	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Full transparency for networks</li> <li>• Operation modes - Set with jumpers</li> </ul>	...
Intelligent image analysis	...	<ul style="list-style-type: none"> <li>• classification of people and vehicles</li> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• intrusion</li> <li>• abandoned/missing object</li> <li>• illegal parking</li> <li>• people counting</li> <li>• detection of people gathering</li> <li>• heat map</li> <li>• detection of loitering in a given area</li> <li>• running</li> <li>• protective helmet detection</li> <li>• detection of persons on duty</li> <li>• face detection</li> <li>• video tampering</li> <li>• Intelligent Object Tracking</li> </ul>
Operation temp	-25 °C ... 65 °C	...



Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• Image rotation and mirror</li> <li>• Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions</li> </ul>
Power supply	ETH-2WIRE-TX : <ul style="list-style-type: none"> <li>• 44 ... 56 V DC - PoE</li> <li>• 24 ... 56 V DC - Power</li> </ul> ETH-2WIRE-RX : <ul style="list-style-type: none"> <li>• 24 ... 56 V - Power</li> <li>• The output PoE voltage is equal to the input voltage</li> </ul>	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC</li> </ul>
Power consumption	1.35 W (total)	≤ 19.4 W
Housing	Plastic (PC)	Speed Dome, Aluminum
Color	...	White + Black
Operation temp	...	-30 °C ... 65 °C
"Index of Protection"	IP20	IP66
Vandal-proof	...	—
Weight	0.03 kg (single element)	3 kg
Dimensions	51 x 51 x 24 mm (single element)	Ø 161 x 276 mm

Supported languages	...	Polish, English, Albanian, Arabic, Korean, French, Hebrew, Spanish, Dutch, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	ATTE	TIANDY
Guarantee	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00