



	MOUNTING SCREWS SM-6/RACK	OVERVOLTAGE LIMITER AXON-NET/PROF	WIRELESS DOORBELL WDP-12A3 EURA	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE78H0T- IT3F(2.8MM)(C) - 5 Mpx Hikvision
				
	243.81 HUF 243.81 HUF	15896.19 HUF 15896.19 HUF	4676.19 HUF 4676.19 HUF	30000.00 HUF 30000.00 HUF
Rated voltage	...	5 V
Maximal voltage	...	6 V
Application	Rack 19" / Rack 10"
Signaling mode	Optical - sound signaling	...
Number of ring-tones	32	...
Voltage protection level line-line	...	40 V ... 1 kV/μs
Volume adjustment	—	...
Standard	AHD / HD-CVI / HD-TVI / CVBS
Operation range	max. 50 m in open area	...
Sensor	Progressive Scan CMOS
Voltage protection level line-PG	...	600 V ... 1 kV/μs
Frequency band	433.92 MHz	...
Matrix size	5 Mpx
Package includes	<ul style="list-style-type: none"> • 4 x M6 screw, • 4 x cage nut, • 4 x plastic shoulder washer, which protects the varnish coating of panels from damage during tightening the screws
Nominal discharge current (line-line)	...	20 A (10/1000μs)
Transmitter power	< 5 mW	...
Material	Steel galvanized
Nominal discharge current (line-PG)	...	20 A (10/1000μs)
Protected pairs of wires	...	1-2, 3-6, 4-5, 7-8
Sockets type	...	RJ45 (8P8C)
Norm	...	Compliance with PN-EN61643-21
Battery power supply	<ul style="list-style-type: none"> • Battery CR2032 3V (included) - Doorbell button, • 2 x Battery 1.5 V LR6 (AA) (not included) - Wireless doorbell 	...
Main features	<ul style="list-style-type: none"> • The number of connected doorbells and cooperated buttons can be increased as required • Volume max. 80 dB / 1 m • Low power consumption 	...

Resolution	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI, • 1920 x 1080 - 1080p @ HD-TVI • 960 x 576 - 960H @ PAL
Range of IR illumination	40 m
IR illuminator power adjustment	Automatic
Lens	2.8 mm
Operation temp	<ul style="list-style-type: none"> • -10 °C ... 35 °C Doorbell button, • 0 °C ... 35 °C Wireless doorbell 	...
View angle	<ul style="list-style-type: none"> • 85 ° (manufacturer data) • 80 ° (our tests result)
IR illuminator support	ICR - Movable InfraRed filter
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 V _{pp} / 75 Ω
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	OSD menu available via recorder
Power supply	12 V DC / 340 mA
Power consumption	≤ 4.3 W
Housing	...	Metal, black	...	Dome, Metal + Plastic
Color	White
"Index of Protection"	<ul style="list-style-type: none"> • IP44 - Doorbell button • IP20 - Wireless doorbell 	IP67
Vandal-proof	—
Operation temp	-40 °C ... 60 °C
Weight	0.037 kg	0.17 kg	<ul style="list-style-type: none"> • 0.034 kg - Doorbell button • 0.058 kg - Wireless doorbell 	0.3 kg



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	...	94 x 50 x 31 mm	<ul style="list-style-type: none"> • 38 x 81 x 23 mm - Doorbell button • 64 x 78 x 32 mm - Wireless doorbell 	Ø 110 x 91 mm
Manufacturer / Brand	EURA	Hikvision
SAP Code	300613613
Guarantee	2 years	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00