



	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW2501T-Z-A-27135-S2 - 5 Mpx 2.7 ... 13.5 mm - MOTOZOOM DAHUA	ELECTRIC ENERGY METER OR-WE-512 ONE-PHASE ORNO
		
	2475.14 NOK 2475.14 NOK	294.86 NOK 294.86 NOK
Device type	...	Electric Energy Meter, One-phase
Standard	AHD, HD-CVI, HD-TVI, PAL	...
Sensor	1/2.7 " Progressive Scan CMOS	...
Rated voltage	...	230 V AC, 50 Hz
Matrix size	5 Mpx	...
Measurement unit	...	kWh
Current	...	5 A - Base current 100 A - Max. current
LCD display	...	5+1 digits (00000.0 kWh)
Measuring accuracy	...	0.001 kWh
Impulse frequency	...	1000 imp/kWh
RS-485 ports	...	—
Connectors type	...	screw terminals
Main features	...	The kit includes two clamp seals to protect the meter connectors
Resolution	2880 x 1620 - 5 Mpx - HD-CVI only : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p - HD-CVI only , 960 x 576 - 960H, PAL	...
Width in 17.5 mm modules	...	1
Lens	2.7 ... 13.5 mm - Motozoom	...
View angle	• 113 ° ... 31 ° (manufacturer data) • 110 ° ... 32 ° @ HD-CVI, 94 ° ... 29 ° @ AHD, HD-TVI (our tests result)	...
Range of IR illumination	60 m	...
IR illuminator power adjustment	Automatic	...
Video output	AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω	...

Audio	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only 	...
S/N ratio	> 65 dB	...
Main features	<ul style="list-style-type: none"> • Motozoom lens - The control possible only from Dahua recorders in HD-CVI mode • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • F-DNR (Defog) - Reduction of image noise caused by precipitation • Mirror - Mirror image • Sharpness - sharper image outlines • D-ZOOM - Digital Zoom : 4 x • Privacy zones - max. 8 	...
OSD menu	OSD menu available via DAHUA recorder	...
Power supply	12 V DC / 660 mA	...
Power consumption	≤ 7.9 W	...
Housing	Dome, Aluminum	Plastic, DIN, TS-35 rail mounting
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.6 kg	0.096 kg
Dimensions	Ø 122 x 105 mm	17.7 x 95 x 75 mm
Manufacturer / Brand	DAHUA	ORNO
Guarantee	5 years	2 years