




	TV OR MONITOR MOUNT BRATECK-LCD-501N	NVR NVR4432-4KS2/I 32 CHANNELS DAHUA	EXPANSION PLUG KW-10/6X100 KLIMAS
			
	14.76 PLN 14.76 PLN	3439.00 PLN 3439.00 PLN	1.03 PLN 1.03 PLN
Standard	...	TCP/IP	...
Mounting standard	VESA 75, 100
Supported resolutions	...	max. 16 Mpx - 4000 x 4000 px	...
Screen size range	max. 32 "
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized
Bearing capacity	30 kg
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA	...
Drilling diameter	10 mm
Distance from mounting surface	88 mm from wall
Expansion plug length	60 mm
Color	Black
Audio support	...	32 Channels - Audio from cameras	...
Audio inputs	...	1 pcs CINCH	...
Tilt adjustment	-15 ° ... 15 °
Audio outputs	...	1 pcs CINCH	...
Screw dimensions	Ø 6 x 100 mm, PZ-3
Horizontal rotation	-24 ° ... 24 °
Rotation in the plane of the screen	—
Application	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Supported hard drives	...	4 x 10 TB SATA	...
Recording modes	...	Manual, Sensor, Motion detection, Schedule	...
Network protocols	...	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Center, IP Search, P2P, ONVIF	...
External storage devices backup	...	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow	...
Bitrate	...	max. 256 Mbps	...
Network functions	...	Full support via network, Remote records copying, Web-Server built-in	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application	...
Default IP address	...	192.168.1.108	...
Default admin user / password	...	admin / -	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Web browser access ports	...	80, 37777	...
PC client access ports	...	37777	...
Mobile client access ports	...	37777	...
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Alarm inputs / outputs	...	16 / 4	...
PTZ control	...	RS-485 - Pelco-P, Pelco-D and others IP Speed Dome Cameras	...
Motion Detection	...	✓	...
RS-485 interface	...	PTZ control function	...
RS-232 interface	...	✓	...
USB	...	1 pcs USB 2.0 1 pcs USB 3.0	...
Intelligent image analysis	...	✓	...
Main features	...	<ul style="list-style-type: none"> • Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians, • Support for devices with the ANPR vehicle identification functions and face recognition, • Heat map - the selection in the image by corresponding colors the areas with different traffic • people counting • SMD PLUS - searching for an object classified as: human, motor vehicle, • face detection • Support for up to 10 face databases, including 20 000 face images • supports 6 types of facial attributes extraction • Face recognition and analysis in real time (up to 12 photos per second) : <ul style="list-style-type: none"> - Comparison of faces with images from the database - Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) • Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity 	...
Mouse support	...	✓	...
IR remote controller in the set	...	—	...
Power supply	...	100 ... 240 V AC, 50 / 60 Hz	...
Power consumption	...	≤ 8 W (without HDD)	...
Operation temp	...	-10 °C ... 55 °C	...
Weight	0.524 kg	4.32 kg	...
Dimensions	115 x 115 x 88 mm	440 x 411 x 76 mm	...
Supported languages	...	Polish, English	...
Country of origin	...	China	...
Manufacturer / Brand	BRATECK	DAHUA	KLIMAS
Guarantee	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00