





	POWER SUPPLY ADAPTER PSC-12010/PRO 12 V DC 1 A	TOOL BOX KHV40P	RFID PROXIMITY CARD ATLO-114	SMART LED LIGHTING CONTROLLER WLIGHTBOX- V3/BLEBOX Wi-Fi_12 ... 24 V DC
				
	7.30 EUR 7.30 EUR	8.09 EUR 8.09 EUR	0.56 EUR 0.56 EUR	29.69 EUR 29.69 EUR
Adapter type	Switching
Standard	Unique EM 125kHz	...
Output voltage	12 V DC
Material	...	Plastic - mixture of increased strength polymers
Compatibility	EM4100/4102	...
Maximal load	1 A
Application	Works with LED lighting - (RGB/RGBW/RGBCCT/CCT/MONO) 12-24V LED strips
Possibility of programming the serial number (ID)	—	...
Average active efficiency	83 %
Ability to write to internal memory	—	...
Output power	12 W
Rated voltage	12 ... 24 V DC
Serial Number overprint	—	...
Power consumption at no- load	< 0.1 W
Maximal total load	360 W
Power connectors type	2.1/5.5 mm - Straight plug
Total maximal current	15 A (3 A / Channel)
Power voltage	100 ... 240 V AC
Number of inputs	1
Number of outputs	1 pcs	5
Housing type	Plastic
Connector type	screw terminals
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
External dimensions	...	384 x 335 x 144 mm
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS
Internal dimensions	...	365 x 245 x 110 mm

Main features	<ul style="list-style-type: none"> • Short-circuit protection • Overload protection • The device has very small dimensions • Length of the cables : 40 + 15 cm 	<ul style="list-style-type: none"> • High-strength body, • Ergonomic handle, • Protective foam inside to protect tools, • Capacity : 10 kg, • 2 fasteners on the front to prevent accidental opening 	<ul style="list-style-type: none"> • Range : ~ 15 cm • The TK-4100 chip 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • Controlling the color, color temperature, brightness, effect, changing time allows any interior arrangement • predefined effects, • effects modification, • Operation modes : <ul style="list-style-type: none"> - 1 x RGB (color) - 1 x RGBW (color + white - brightness control) - 1 x RGBWW / RGB CCT (color + white - brightness and color temperature control) - 1 x RGB (color) + 1 x MONO (single color) - 1 x CCT (white - brightness and color temperature control) - 2 x CCT (white - brightness and color temperature control) - 1 x RGB (color) + 1 x CCT (white - brightness and color temperature control) - 5 x MONO (single color) / halogen bulb • µWiFi technology support
Housing	Plastic
"Index of Protection"	IP67	IP20
Color	...	Black	...	Black
Operation temp	0 °C ... 40 °C	-20 °C ... 50 °C
Weight	0.12 kg	0.95 kg	0.006 kg	0.026 kg
Dimensions	57 x 40 x 26 mm	...	85 x 54 x 2 mm	43 x 35 x 18 mm
Manufacturer / Brand	ATLO	BleBox
Guarantee	2 years	2 years	2 years	2 years