





| | AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA25FSR3-G(H2) - 5 Mpx 2.8 mm | MULTI-FUNCTIONAL USB TESTER SP-UT01 Spacetronek | TV OR MONITOR MOUNT BRATECK-KL21G-46T | HUB USB 3.0 PAPW4A-U3-015-BK-EP |
|-------------------------------------|---|---|--|---|
| |  |  |  |  |
| | 44.35 CHF 44.35 CHF | 23.51 CHF 23.51 CHF | 6.84 CHF 6.84 CHF | 6.84 CHF 6.84 CHF |
| Device type | ... | Power meter via USB, USB-C, micro USB ports | ... | ... |
| Input socket type | ... | 1 x USB-A plug 1 x USB-C plug 1 x microSD socket | ... | ... |
| Connectors | ... | ... | ... | • 1 x plug - USB-A • 4 x socket - USB-A |
| Standard | AHD / HD-CVI / HD-TVI / CVBS | ... | ... | ... |
| Length of the cable | ... | ... | ... | 15 cm |
| Output socket type | ... | 1 x USB-A socket 1 x USB-C socket | ... | ... |
| USB standard | ... | ... | ... | 3.0 |
| LCD display | ... | 0.96 " | ... | ... |
| Mounting standard | ... | ... | VESA : 100, 200 x 100, 200, 300, 400 x 200, 400, 600 x 400 | ... |
| DC voltage measurement | ... | 3.6 ... 32 V @ 0.01 V | ... | ... |
| Screen size range | ... | ... | 37 " ... 70 " | ... |
| Bearing capacity | ... | ... | 40 kg | ... |
| Distance from mounting surface | ... | ... | 53 mm | ... |
| DC current measurement | ... | 0 ... 5.1 A @ 0.01 A | ... | ... |
| Tilt adjustment | ... | ... | -12 ° ... 12 ° | ... |
| Power measurement | ... | 0 ... 150 W @ 0.01 W | ... | ... |
| Horizontal rotation | ... | ... | — | ... |
| Rotation in the plane of the screen | ... | ... | — | ... |
| Battery capacity measurement | ... | 0 ... 99999 mAh @ 1 mAh | ... | ... |
| Impedance measurement | ... | 1 ... 999.9 Ω @ 0.1 Ω | ... | ... |
| Resolution | • 2704 x 1950 - 5 Mpx @ AHD / HD-TVI - 20 fps • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI - 25 fps • 960 x 576 - 960H @ PAL | ... | ... | ... |
| Temperature measurement | ... | 0 ... 80 °C @ 1 °C | ... | ... |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | |
|---|---|--|-------------------|-----------------|
| Sensor | 1/2.8 " STARVIS™ CMOS | ... | ... | ... |
| Lens | 2.8 mm | ... | ... | ... |
| View angle | 103 ° | ... | ... | ... |
| Range of IR illumination | 30 m | ... | ... | ... |
| Time display range | ... | max. 999 h 59 min 59 s @ 1 s | ... | ... |
| Maximal load | ... | 150 W | ... | ... |
| Range of displayed cumulative electricity | ... | 0.000 ... 999999 mWh @ 1 mWh | ... | ... |
| Video output | AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω | ... | ... | ... |
| Audio | <ul style="list-style-type: none"> • Microphone built-in • Audio output | ... | ... | ... |
| OSD menu | ✓ | ... | ... | ... |
| Standards | ... | PD2.0, PD3.0, QC2.0, QC3.0, BC1.2 and others | ... | ... |
| Main features | <ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • Auto White Balance • AGC - Automatic Gain Control • 3D-DNR - Digital Noise Reduction • Day/night mode • ICR - Movable InfraRed filter | ... | ... | ... |
| Power supply | 12 V DC / 416 mA | 3.6 V DC - Port USB | ... | ... |
| Power consumption | < 5 W | ... | ... | ... |
| Housing | Dome, Metal | Plastic | ... | ... |
| Color | Graphite | ... | Black | ... |
| "Index of Protection" | IP66 | ... | ... | ... |
| Mechanical protection class | — | ... | ... | ... |
| Operation temp | -20 °C ... 60 °C | ... | ... | ... |
| Weight | 0.3 kg | 0.17 kg | 1.74 kg | 0.035 kg |
| Dimensions | Ø 94 x 80 mm | 67 x 61 x 11 mm | 643 x 425 x 53 mm | 98 x 34 x 13 mm |
| Supported languages | Polish, English | ... | ... | ... |
| Manufacturer / Brand | BCS UNIVERSAL | Spacetronek | BRATECK | ORICO |
| Guarantee | 3 years | 2 years | 2 years | 2 years |