



	POWER DISTRIBUTION UNIT AK-SP-05B AKYGA	ACCESS CONTROLLER MODULE MC16-PAC-ST-1 ROGER
		
	9.03 EUR 9.03 EUR	249.86 EUR 249.86 EUR
Rated voltage	230 V AC / 50 Hz	...
Number of served transitions	...	1 (two-way)
Total maximal current	10 A	...
Number of supported readers	...	4
Maximal total load	2500 W	...
Response time	< 25 ns	...
Number of users	...	unlimited (purchase of the appropriate license required)
Number of outlets	5 grounded outlets 10A/250V	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Automatic delayed fuse	10 A / 250 V	...
Buffer memory	...	8 000 000 events buffer
Number of access zones	...	2
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Number of alarm zones	...	2
DC filter to eliminate interferences	RFI ≤ 10 dB	...
Battery backup support	...	12 V / 7 Ah
Maximum stroke current	4.5 kA	...
Maximum energy absorption	150 J	...
Switch	with light indication	...
Communication	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface
Length of the cable	3.0 m	...
Housing	Plastic (ABS)	...
Color	Black	...

Main features	...	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128
Power supply	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	5 °C ... 50 °C	5 °C ... 40 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)
Weight	0.372 kg	0.14 kg
Dimensions	305 x 50 x 40 mm	175 x 72 x 30 mm
Manufacturer / Brand	AKYGA	ROGER
Guarantee	2 years	3 years