



	WI-FI SMART PLUG ATLO-S1IP5-TUYA Wi-Fi, Tuya Smart	SMART DUAL VALVE FOR THE IRRIGATION SYSTEM ATLO-VR2G-BLE-TUYA Bluetooth BLE, Tuya Smart
		
	5908.57 HUF 5908.57 HUF	20457.14 HUF 20457.14 HUF
Application	...	irrigation control - 2 Zones
Rated voltage	100 ... 250 V, 50 / 60 Hz	...
Type (size)	...	3/4 "
Maximal total load	4000 W	...
Total maximal current	16 A	...
Number of outlets	1 pcs	...
Working pressure	...	0.05 ... 0.8 MPa / 7.25 ... 116 psi
Socket type	CEE 7/3 (Schuko)	...
Grounding	✓	...
Opening/closing time	...	5 ... 10 s
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	<ul style="list-style-type: none"> • Bluetooth, • 2.4 GHz Wi-Fi IEEE 802.11 b/g/n - Bluetooth/Wi-Fi gateway
Radio communication range (at open area)	...	<ul style="list-style-type: none"> • 15 m - Bluetooth • The range limited only by the availability of the Wi-Fi network - Bluetooth/Wi-Fi gateway
Mobile phones support	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Manufacturer / Brand	ATLO	...

Main features	<ul style="list-style-type: none"> • schedule, • timer, • remote access, • voice control • Away Mode - automatically turns devices on and off at different times to give the appearance that someone is home • Easy operation • ON/OFF button • STATUS indicator • Built-in Bluetooth module that allows you to control the device in case of loss of connection to the WiFi network 	<ul style="list-style-type: none"> • schedule, • timer, • manual watering (app or button), • delay after rain : 1 ... 7 days - the device will not turn on the sprinklers if it is raining, • remote access - Bluetooth/Wi-Fi gateway (included), • voice control • 2 x STATUS indicator • Low current consumption • Easy installation - the valve is mounted directly on the tap • 2 x 3/4" / 1/2" Adapter (included)
Housing	Plastic	Plastic (ABS) + Nylon, UV-resistant, Waterproof
"Index of Protection"	IP55	IP55
Color	White	Gray + Black
Power supply	...	4 x 1.5V, type AA/LR6/FR6 battery (not included)
Operation temp	-20 °C ... 60 °C	4.5 °C ... 45 °C
Weight	0.178 kg	0.4 kg
Dimensions	96 x 70 x 65 mm	141 x 122 x 58 mm
Guarantee	2 years	2 years