




	<a href="#">AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA HAC-HDBW1500E-0280B-S2 - 5 Mpx 2.8 mm DAHUA</a>	<a href="#">ISOPROPYL ALCOHOL CLEANSER-IPA/100 BOTTLE 100 ml</a>	<a href="#">PANEL WITH CABLE ENTRY A19-PK-V2</a>
			
	91.29 CHF 91.29 CHF	2.65 CHF 2.65 CHF	5.16 CHF 5.16 CHF
Width	...	...	19 "
Height	...	...	1 U
Package	...	Bottle 100 ml	...
Material	...	...	Steel - powder painted
Standard	AHD / HD-CVI / HD-TVI / CVBS	...	...
Sensor	1/2.7 " Progressive Scan CMOS	...	...
Application	...	...	RACK 19"
Matrix size	5 Mpx	...	...
Main features	...	...	<ul style="list-style-type: none"> <li>• Dimensions of the cable entry hole : 380 x 30 mm (one edge open)</li> <li>• The entry is covered with a brush</li> <li>• 4-point fixing to the front RACK rails</li> <li>• 4 pcs. of M6 screws with cage nuts included</li> <li>• Corrosion resistance</li> </ul>
Resolution	2880 x 1620 - 5 Mpx @ HD-CVI : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 960 x 576 - 960H, PAL	...	...
Range of IR illumination	30 m	...	...
IR illuminator power adjustment	Automatic	...	...
Lens	2.8 mm, F1.85	...	...
View angle	<ul style="list-style-type: none"> <li>• 98 ° (manufacturer data)</li> <li>• 103 ° @ HD-CVI / 90 ° @ AHD / HD-TVI (our tests result)</li> </ul>	...	...
IR illuminator support	ICR - Movable InfraRed filter	...	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...	...

Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2-DNR - Digital Noise Reduction</li> <li>• BLC - configurable Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Day/night mode</li> <li>• Auto White Balance</li> <li>• Privacy zones</li> </ul>	...	...
OSD menu	OSD menu available via recorder	...	...
Power supply	12 V DC / 330 mA	...	...
Power consumption	≤ 4.2 W	...	...
Housing	Dome, Metal	...	...
Color	White	...	Black (RAL 9005)
"Index of Protection"	IP67	...	...
Vandal-proof	IK10	...	...
Operation temp	-40 °C ... 60 °C	...	...
Weight	0.33 kg	0.09 kg	0.21 kg
Dimensions	Ø 110 x 81 mm	Ø 50 x 105 mm	483 x 44 x 12 mm
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Italian	...	...
Manufacturer / Brand	DAHUA	...	...
Guarantee	3 years	...	2 years