



	<a href="#">NVR APTI-N3224AI-I3 32 CHANNELS</a>	<a href="#">DISK ARRAY ESS1504C 24 TB DAHUA</a>
		
	307.26 EUR 307.26 EUR	708.31 EUR 708.31 EUR
Standard	TCP/IP	...
Supported resolutions	max. 12 Mpx - 4000 x 3000 px	...
Video outputs	1 pcs HDMI 4K 1 pcs VGA	...
Audio support	<ul style="list-style-type: none"> <li>• 32 Channels - Audio from cameras,</li> <li>• Bi-directional audio streaming support</li> <li>• Compliance with the AAC standard</li> </ul>	...
Outputs	...	<ul style="list-style-type: none"> <li>• 1 x eSATA - 3 Gb/s (DVR)</li> <li>• 1 x USB 3.0 B (computer)</li> </ul>
Audio inputs	1 pcs CINCH	...
Write transfer rate	...	64 MB/s
Audio outputs	1 pcs CINCH	...
Read speed	...	64 MB/s
Image compression method	H.265+ / H.265 / H.264+ / H.264	...
Bitrate	320 Mbps	...
Supported hard drives	4 x 10 TB SATA	4 x SATA - max. 24 TB (total)
Permissible relative humidity	...	10 % ... 90 %
Recording modes	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	Records backup at (.avi) format to USB (pendrive)	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast Playback max. 16 cameras in the same time @ 1080p	...
Network interface	2 x RJ-45 10/100/1000 Base-TX	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network protocols	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE	...
ONVIF	✓	...
Default IP address	192.168.1.88	...
Default admin user / password	admin / 12345	...
Web browser access ports	80, 5000, 554	...
PC client access ports	80, 5000, 554	...
Mobile phones support	Access by a cloud (P2P) • Android: Free application <a href="#">BitVision</a> , Android: Free application <a href="#">iVMS320</a> • Android: Free application <a href="#">BitVision</a> , iOS: Free application <a href="#">iVMS320</a>	...
USB	• 2 pcs USB 2.0 • 1 pcs USB 3.0	...
Serial ports	RS-485	...
Alarm inputs / outputs	16 / 4	...
PTZ control	• IP Speed Dome Cameras • RS-485 control	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...
Intelligent image analysis	✓	...
Main features	• Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom	...
Mouse support	✓	...
IR remote controller in the set	—	...
Switch PoE	—	...
Power supply	100 ... 240 V AC, 50 / 60 Hz	100 V ... 240 V AC
Power consumption	≤ 20 W (without HDD)	6.8 W (without HDD)
Operation temp	-10 °C ... 50 °C	0 °C ... 40 °C
Weight	4.38 kg	4.29 kg
Dimensions	440 x 372 x 69 mm	440 x 408 x 70 mm - RACK 19", 1.5U
Supported languages	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Ukrainian, Italian	...
Manufacturer / Brand	APTI	DAHUA
Guarantee	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel.:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00