

	IP VANDALPROOF CAMERA IPC-HDBW5442E-ZE-2712-DC12AC24V-BLACK WizMind - 4 Mpx, 2.7 ... 12 mm - MOTOZOOM DAHUA	HDD ENCLOSURE 25PW1-U3-BK-EP ORICO
		
	7441.47 NOK 7441.47 NOK	87.73 NOK 87.73 NOK
Standard	TCP/IP	...
Sensor	1/1.8 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
Supported hard drives	...	1 x SATA III, 2.5 " - 6 TB (max)
Outputs	...	1 x USB 3.0 Micro B, max. 5 Gb/s
Operation state indication	...	LED diodes
Resolution	2688 x 1520 - 4 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Lens	2.7 ... 12 mm - Motozoom	...
View angle	• 114 ° ... 47 ° (manufacturer data) • 103 ° ... 46 ° (our tests result)	...
Range of IR illumination	40 m	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	AI H.265 / H.265+ / H.265 / AI H.264 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Audio detection • Bi-directional audio streaming support • Compliance with the AAC standard 	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	HTTP, HTTPS, TCP, IPv4/IPv6, ARP, RTCP, RTSP, RTP, RTMP, UDP, SMTP, FTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP Bonjour	...
WEB Server	Built-in, Web Viewer	...
Max. number of on-line users	20	...
ONVIF	20.12	...
Main stream frame rate	25 fps @ 4 Mpx	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS 	...
Default IP address	192.168.1.108	...

Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • Motozoom lens • WDR - 140 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Motion Detection • Configurable Privacy Zones • ICR - Movable InfraRed filter • Image rotation and mirror • NAS - Network Attached Storage support • SSA - Smart Scene Adaptive - intelligent scene adaptation by automatically adjusting the exposure parameters to obtain a better image • SMD 3.0 - searching for an object classified as: human, motor vehicle • Heat map - the selection in the image by corresponding colors the areas with different traffic • IVS analysis : crossing the line (tripwire), intrusion, fast moving - classification of people and vehicles, detection of people gathering, loitering detection, people counting - detection and maintenance of 4 independent areas, detection of people gathering, face detection - supports 6 types of facial attributes extraction 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • ePoE, • 12 V DC / 980 mA, • 24 V AC / 490 mA 	5 V DC - from USB port
Power consumption	<ul style="list-style-type: none"> • ≤ 12.4 W @ 12 V DC • ≤ 11.9 W @ 24 V AC • ≤ 11.6 W @ PoE 	...
Housing	Dome - Metal	Plastic
Color	Black	...
"Index of Protection"	IP67	...
Vandal-proof	IK10	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.88 kg	0.06 kg
Dimensions	Ø 159 x 118 mm	130 x 80 x 14 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Italian	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Manufacturer / Brand	DAHUA	ORICO
Guarantee	5 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00