



	SWITCH POE HS4408-4ET-96 4-PORT + 4 x SFP DAHUA	POE SWITCH, EXTENDER XPOE-4-11A-HS 4-PORT ATTE
		
	115.63 EUR 115.63 EUR	44.11 EUR 44.11 EUR
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 (10/100/1000 Base-T, 3 PoE (802.3af/at) + 1 PoE (802.3bt) / Hi-PoE / PoE (802.3af/at)) • 4 x Uplink (port SFP - 1000 Base-X) 	<ul style="list-style-type: none"> • 1 x LAN + PoE IN - Port LAN 1, • 3 x LAN + PoE OUT - LAN2 ... LAN4 ports
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 LAN & PoE ports • 1000 SFP ports 	10 / 100 Mbps
Management	✓	—
Maximal output power	<ul style="list-style-type: none"> • 30 W / port PoE 802.3af/at • 90 W / port PoE 802.3bt 	<ul style="list-style-type: none"> • 40 W @ Passive PoE - LAN2 ... LAN4 ports • 13 W / 25 W @ PoE (802.3af/at) - LAN2 ... LAN4 ports
Maximal total power	96 W	...
Operation modes	<ul style="list-style-type: none"> • Extend On : 250 m, 10 Mbps • Extend Off : 100 m, 10 / 100 Mbps 	...

Main features	<ul style="list-style-type: none"> • DIN, TS-35 rail mounting • Data Flow Control • protection against lightning discharges and voltage differences and strokes between devices • Industrial wide temperature design. • Intelligent management of Power Supply Unit power's output stage • PoE (802.3af), PoE (802.3at), Hi-PoE, PoE (802.3bt) • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • The ability to connect two power adapters - redundant power supply • The device supports 8-pin power supply 	<ul style="list-style-type: none"> • Possibility to power up to 3 PoE 802.3at/af or PASSIVE receivers • Possibility to connecting in cascade • The ability to turn off the power on selected PoE ports • The output PoE voltage is equal to the input voltage • Overvoltage protection • Short-circuit protection - LAN 1
LED diodes	Power, Link/Act, PoE	Power, LAN
Certificates	CE	...
Power supply	48 ... 57 V DC (power adapter included)	<ul style="list-style-type: none"> • 44 ... 56 V DC - LAN 1, • 12 ... 56 V DC - LAN 2 ... LAN 4
Housing type	DIN	...
Operation temp	-30 °C ... 65 °C	...
Weight	0.618 kg	0.04 kg
Dimensions	150 x 110 x 42 mm	94 x 41 x 18 mm
Manufacturer / Brand	DAHUA	ATTE
Guarantee	3 years	3 years