





| | RFID PROXIMITY CARD ATLO-104N*P200 | EXPANSION PLUG KS-12/8X60 KLIMAS | COVER PLATE A19-MASK | IP CAMERA APTI-AI802C4-36W - 8.3 Mpx 4K UHD 3.6 mm | KRONE BACK-MOUNT FRAME LSA-GN-10/3 |
|---|--|---|---|--|---|
| |  |  |  |  |  |
| | 60.03 EUR 60.03 EUR | 0.29 EUR 0.29 EUR | 2.22 EUR 2.22 EUR | 94.13 EUR 94.13 EUR | 1.87 EUR 1.87 EUR |
| Standard | ... | ... | ... | IP | ... |
| Number of mounted profile modules | ... | ... | ... | ... | 3 pcs |
| Type of mounted profile modules | ... | ... | ... | ... | 10PAR |
| In package | 200 pcs The price for package | ... | ... | ... | ... |
| Material | ... | <ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized | ... | ... | ... |
| Drilling diameter | ... | 12 mm | ... | ... | ... |
| Standard | Unique EM 125kHz | ... | ... | ... | ... |
| Expansion plug length | ... | 60 mm | ... | ... | ... |
| Compatibility | EM4100/4102 | ... | ... | ... | ... |
| Possibility of programming the serial number (ID) | — | ... | ... | ... | ... |
| Ability to write to internal memory | — | ... | ... | ... | ... |
| Screw dimensions | ... | Ø 8 x 60 mm, SW-13 | ... | ... | ... |
| Serial Number overprint | ✓ | ... | ... | ... | ... |
| Application | ... | <ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick | ... | ... | ... |
| Resolution | ... | ... | ... | 3840 x 2160 - 8.3 Mpx 4K UHD , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p | ... |
| Sensor | ... | ... | ... | 1/2.8 " SONY Starvis™ Back-illuminated CMOS | ... |
| Main features | <ul style="list-style-type: none"> Serial Number Format : 8H10D + WEG24A Range : ~ 11 cm The TK-4100 chip | ... | ... | ... | ... |
| Lens | ... | ... | ... | 3.6 mm @ F1.6 | ... |
| View angle | ... | ... | ... | 84 ° | ... |
| Range of IR illumination | ... | ... | ... | 40 m | ... |
| Memory card slot | ... | ... | ... | — | ... |
| Image compression method | ... | ... | ... | H.265+ / H.265 / H.264+ / H.264 / AVI / JPEG | ... |
| Alarm inputs / outputs | ... | ... | ... | — | ... |
| Audio | ... | ... | ... | <ul style="list-style-type: none"> Microphone built-in, Audio transmission via network Compliance with the AAC standard | ... |
| Main stream frame rate | ... | ... | ... | 20 fps @ 8.3 Mpx | ... |
| Interface | ... | ... | ... | 10/100 Base-T (RJ-45) | ... |
| WEB Server | ... | ... | ... | Built-in | ... |
| Max. number of on-line users | ... | ... | ... | 10 | ... |
| ONVIF | ... | ... | ... | 19.12 | ... |
| Intelligent image analysis | ... | ... | ... | <ul style="list-style-type: none"> intrusion - classification of people and vehicles crossing the line (tripwire) - classification of people and vehicles loitering detection (human silhouette) detection of people gathering (human silhouette) motion detection based on human detection | ... |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | | |
|-------------------------------|----------------|---------|-----------------|--|------------------|
| Main features | ... | ... | ... | <ul style="list-style-type: none"> • Day/night mode • ICR - Movable InfraRed filter • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Mirror - Mirror image • 3D-DNR - Digital Noise Reduction • WB - White Balance • Flicker Control - The technology eliminates the tiring eyes flickering image effect • video tampering • HLC - High Light Compensation (spot) • Corridor mode • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • WDR - Wide Dynamic Range • Motion Detection • Privacy zones - max. 3 • AGC - Automatic Gain Control | ... |
| Mobile phones support | ... | ... | ... | Port no.: 80 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision | ... |
| Default IP address | ... | ... | ... | 192.168.1.168 | ... |
| Default admin user / password | ... | ... | ... | admin / admin | ... |
| Web browser access ports | ... | ... | ... | 80 | ... |
| PC client access ports | ... | ... | ... | 80 | ... |
| Mobile client access ports | ... | ... | ... | 80 | ... |
| Port ONVIF | ... | ... | ... | 80 | ... |
| RTSP URL | ... | ... | ... | rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream | ... |
| Power supply | ... | ... | ... | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 950 mA | ... |
| Power consumption | ... | ... | ... | ≤ 11.4 W | ... |
| Housing | ... | ... | ... | Compact - Metal | ... |
| Color | ... | ... | Black | White | ... |
| "Index of Protection" | ... | ... | ... | IP67 | ... |
| Mechanical protection class | ... | ... | ... | — | ... |
| Operation temp | ... | ... | ... | -20 °C ... 60 °C | ... |
| Weight | 0.006 kg | ... | 0.19 kg | 1.12 kg | ... |
| Dimensions | 86 x 54 x 1 mm | ... | 218 x 39 x 2 mm | 268 x 95 x 88 mm | 67 x 112 x 50 mm |
| Supported languages | ... | ... | ... | Polish, English, Bulgarian, Czech, French, Hebrew, Spanish Dutch, German, Portuguese, Russian, Turkish, Italian | ... |
| Manufacturer / Brand | ATLO | KLIMAS | DELTA | APTI | ... |
| Guarantee | 2 years | 2 years | 3 years | 2 years | 2 years |