




	<a href="#">HUB USB 3.0 HUB-USB3.0-1/4 55 cm</a>	<a href="#">RFID PROXIMITY CARD ATLO-114</a>	<a href="#">AHD, HD-CVI, HD-TVI CAMERA BCS-EA25FSR3(H2) - 5 Mpx 2.8 mm</a>
			
	6.24 EUR 6.24 EUR	0.57 EUR 0.57 EUR	46.15 EUR 46.15 EUR
Standard	...	Unique EM 125kHz	...
Compatibility	...	EM4100/4102	...
Possibility of programming the serial number (ID)	...	—	...
Ability to write to internal memory	...	—	...
Standard	...	...	AHD / HD-CVI / HD-TVI / CVBS
Serial Number overprint	...	—	...
Connectors	<ul style="list-style-type: none"> <li>• 1 x socket - USB 3.0 Micro B</li> <li>• 4 x socket - USB 3.0 A</li> <li>• 1 x Power socket - 1.35 / 3.50 mm</li> </ul>	...	...
Length of the cable	55 cm	...	...
USB standard	3.0	...	...
Main features	<ul style="list-style-type: none"> <li>• Solid workmanship</li> <li>• It can be used as a charger for multiple devices when connected to an external power source via the 3.50 / 1.35 mm socket</li> <li>• LED indication</li> <li>• The cable included in the kit: USB 3.0 A plug / USB 3.0 Micro B plug</li> <li>• Each socket has a separate switch</li> </ul>	<ul style="list-style-type: none"> <li>• Range : ~ 15 cm</li> <li>• The TK-4100 chip</li> </ul>	...
Resolution	...	...	2704 x 1950 - 5 Mpx @ AHD / HD-TVI @ 20 fps , 2560 x 1440 - 3.7 Mpx @ AHD / HD-CVI / HD-CVI @ 25 fps 1920 x 1080 - 1080p - AHD, HD-TVI, HD-CVI @ 25 fps
Sensor	...	...	1/2.8 " Progressive Scan CMOS
Lens	...	...	2.8 mm, F1.2
View angle	...	...	103 °
Range of IR illumination	...	...	30 m

S/N ratio	...	...	> 50 dB
Video output	...	...	AHD / HD-CVI / HD-TVI, 1 Vpp / 75 Ω
OSD menu	...	...	✓
Audio	...	...	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio output</li> </ul>
Main features	...	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• BLC - configurable Back Light Compensation</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> </ul>
Power supply	...	...	12 V DC / 420 mA
Power consumption	...	...	< 5 W
Housing	...	...	Dome, Metal
Color	...	...	White
"Index of Protection"	...	...	IP66
Mechanical protection class	...	...	—
Operation temp	...	...	-20 °C ... 60 °C
Weight	0.044 kg	0.006 kg	0.3 kg
Dimensions	105 x 36 x 25 mm	85 x 54 x 2 mm	Ø 94 x 80 mm
Manufacturer / Brand	...	ATLO	BCS
Guarantee	2 years	2 years	3 years